

## This document was generated on 02/29/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:	1300990106 Active Strain-Relief Cord Grips MAX-LOC® Strain Relief Co 15.88-19.05mm (.625750")	ord-Sealing Grip, 3/4" NPT, 90° Angle Male, Cable Diameter , Stainless Steel Mesh	
Documents: Drawing (PDF) RoHS Certificate of Compliance (PDF)		Product Literature (PDF)	
Agency Certification	n	LR32159	Series image - Reference only
General Product Family Series Eye Type NEMA Rating O-Ring Overview Product Literature Or Product Name Type UPC Use With Woodhead	der No	Cable Grips <u>130099</u> N/A NEMA 3R No <u>Strain-Relief Cord Grips</u> 987650-8064 MAX-LOC® Strain Relief Grip 78678855434 3/4" NPT MAX-LOC® Lock Nut <u>130099-0144</u> , 3/4" NPT MAX-LOC® Gasket Sealing Ring <u>130099-0150</u> , 3/4" NPT MAX-LOC® O-Ring <u>130180-0333</u> Yes	Not ReviewedEU RoHSChina RoHSNot ReviewedREACH SVHCNot ReviewedHalogen-FreeStatusNot ReviewedNeed more information on product environmental compliance?Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.China ROHSNot Reviewed
Physical Approximate Break S Bale Length Body Style Cable Diameter Color - Grommet Gender Material - Body Material - Body Material - Grip Mesh Length Number of Holes Thread Size	itrength	317.51kg (700 lbs) N/A 90° Angle 15.88-19.05mm (.625750") Orange Male Nylon Stainless Steel 0.229m (9.00") 1 3/4" NPT	ELV Not Reviewed   Search Parts in this Series   130099 Series
Material Info Old Part Number Reference - Drawing Sales Drawing	g Numbers	5543M SD-130099-004	

This document was generated on 02/29/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Glands, Strain Reliefs & Cord Grips category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 120-116-1-1-20BP
 120-116-1-1-32BE
 120-117-40
 120-123-14
 120-125-16
 120-125-16R
 120-125-16Y
 120-125-24Y
 120-125-24Y

 28
 120-125-28R
 120-125-32
 120-125-32R
 120-125-40
 120-125-56
 120-126-16
 120-126-20
 120-126-20BL
 120-126-20R
 120-