

### Features:

- USA Fixed AC Head
- 1 Year Warranty
- Level VI Efficiency
- Universal Input
- UL Approved
- Small and Compact Design



| SPECIFICATION         |                                      |         |         |
|-----------------------|--------------------------------------|---------|---------|
| Part Number           | T6639ST                              | T6640ST | T6642ST |
| AC Input Voltage      | 90-264VAC                            |         |         |
| AC Input Frequency    | 47-63Hz                              |         |         |
| AC Input Current      | 0.5A Max                             |         |         |
| AC Inrush Current     | No Damage                            |         |         |
| Output Voltage        | +12V                                 | +12V    | +5V     |
| Min Load Current      | 0A                                   |         |         |
| Nominal Load Current  | 1A                                   | 2A      | 2.5A    |
| Nominal Output Power  | 12W                                  | 24W     | 12.5W   |
| Output Regulation     | +-5%                                 |         |         |
| Line Regulation       | +-2%                                 |         |         |
| Ripple & Noise        | 300mV p-p                            |         |         |
| Average Efficiency    | 82%                                  |         |         |
| Rise Time             | 100mS                                |         |         |
| Turn On Delay         | 3s                                   |         |         |
| Size                  | 70 x 30 x 29 mm                      |         |         |
| Weight                | 120g                                 |         |         |
| Input Plug Type       | USA Fixed                            |         |         |
| Output Cord           | 18AWG 1500 Jackplug 5.5 x 2.1 x 12mm |         |         |
| Operating Temperature | 0 - 40 Deg C                         |         |         |
| Storage Temperature   | -20 to 60 Deg C                      |         |         |
| Operating Humidity    | 20 - 85%                             |         |         |
| Storage Humidity      | 5 - 95%                              |         |         |
| Hi Pot                | 3000VAC 10mA 1 Min                   |         |         |
| Leakage Current       | 0.25mA Max                           |         |         |
| Safety                | UL                                   |         |         |
| EMI                   | EN55022                              |         |         |
| MTBF                  | 50K Hours                            |         |         |



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wall Mount AC Adapters](#) category:*

*Click to view products by [Stadium Group](#) manufacturer:*

Other Similar products are found below :

[76000738](#) [76000756-B10](#) [ADP-163 E](#) [ADP-159 A](#) [PSAC05A-050L6](#) [RLMDT361800](#) [TE30A1803F01](#) [0650-00005](#) [P25A14E-R1C](#) [SWI24-12-N-P6R](#) [TRH25033-A-02E01-Level-VI](#) [DA5-050US-B](#) [DA5-050UK-B](#) [RLMDT701800](#) [76000756](#) [DA5-050EU-B](#) [WSU120-2000-R13](#) [5V1A-USB](#) [AC-DC ADAPTER 160W](#) [WSU120-2000-13](#) [WSU150-0800-13](#) [76000980](#) [WSU075-3200-13](#) [WSU090-2500-13](#) [WSU050-2000-R13](#) [WSU240-1000-13](#) [WSU090-3500-R13](#) [WSU075-1500-13](#) [WSU135-1330-13](#) [WSU045-1500-13](#) [WSU090-2500-R13](#) [WSU240-1500-13](#) [WSU180-0660-13](#) [WSU075-1500-R13](#) [WSU090-1300-13](#) [WSU180-1330-R13](#) [NTPS-24-TT-700](#) [BB-SMI1812VP230C1](#) [WSU150-1600-13](#) [WSU050-1500-13](#) [WSU090-0800-13](#) [WSU180-0450-13](#) [WSU150-0560-R13](#) [WSU135-0880-13](#) [WSU120-3000-13](#) [WSU120-1000-R13](#) [WSU090-1300-R13](#) [WSU060-4000-13](#) [WSU060-1250-13](#) [WSU050-4000-13](#)