

## Datasheet for part number MDM-9PH011F

Our Catalog Part Number: MDM-9PH011F

Brand: Cannon Product Category: Micro Product Line: Micros Series: MICRO

Product Datasheet	
Series	Micro "D" Metal Shell
Arrangement	9 Contact
Gender	Pin
Contact Material	gold plated copper alloy
Contact Typ	crimp
Contact Resistance	8 milliohms max.
Termination Type	36" Min, M16874/4 #26AWG, Yellow
Shell Material	Aluminum
Shell Finish	Yellow Chromate/Cadmium over Nickel
Insulator Material	contact size 9 to100 = liquid crystalline polymer, contact arrangements 7C2 or 24C4 = Diallyl phthalate
Hardware	Float Mount
Coupling	Friction Coupling
Current Rating	3 A max.
Dielectric Withstanding Voltage	600 VAC at sea level 150 VAC at 70,00' altitude
Insulator Resistance	5000 megohms min.
Thermal Shock	-55°/+125°
Physical Shock	50 G's, 3 axes, 6 milisecond duration sawtooth pulse
Vibration	20G's, 10-2000 Hz. 12 hours
Durability	500 cycles of mating and unmating, 500 CPH max.
Moisture Resistance	Insulator resistance > 100 megohms
SaltSpray	48 hours
Disclaimer	Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub MIL Spec Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

M24308/4-13Z M8351307-B D38999/20FJ43HN D38999/24WG11PB-LC D38999/24WG41HN MDM-15PH041P MDM-21PH041P MDM-21SH003B-K139 850-056-0812 1218697-4 DBMM25S MS27467T21F41S 17D25HV 1996840-1 243082-15 1663962-1 1757682-1 17D-E51218-1 17SDA15S 1883533-1 1883886-1 1883889-1 192900-0377 308-CP6P0441-024H M24308/2-3Z M24308/4-3Z M24308/4-4F M24308/4-4Z M24308/8-347 M83513/03-E09C M83723/75W2212N L/C D38999/24FJ29PN-LC D38999/24WG11SB-LC MDM-21PH046P 5-1218949-1 550-031NF1R6K 550E001NF1R3J0L 550T001NF1R6K0L 557T283NF5B08 C115368-1612B C115370-1717B DC121073157 443869-3 443869-4 443869-5 550S004NF1R1B0F03 550-031NF1R2E 550E003M2R9J0F04 550E003M3R9J0F05 550E024M104R9J0