

Unipolar flexible cables



RoHS
Conformity

Applications:
Unipolar flexible cable for electronics.

Characteristics:
 Conductor: O.F.C. red copper
 C130 PVC
 Insulation: C131 PVC HT 105°
 Sheath colours: **White, Brown, Green, Yellow, Grey, Pink, Blue, Red, Black, Violet**

| tasker® Code | Cond. number | Nominal section mm² | Nominal section AWG | Cond. Format. mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|---------------------|---------------------|-------------------|-----------------------------|---------------------------|------|-----|
| | | | | | | mt. | Type | Kg. |
| C130 | 1 | 1 x 0,22 | 24 | 7x0,20 | 1,2 | 200 | B | 0,7 |
| C131 | | 1 x 0,35 | 22 | 11x0,20 | 1,4 PVC HT 105° | 200 | B | 1,0 |

Production on demand

RoHS
Conformity

| Conductor Resistance | Max rated Voltage | Operative Temperature |
|----------------------|-------------------|-----------------------|
| Ω/Km ± 5% | AC - V | °C |
| 90 | 49 | -15 / +70 |
| 60 | 49 | -15 / +90 |

Unipolar cable with Stiff Wire 6/10



Applications:
Unipolar cable with stiff wire 6/10 in tinned copper for electronics.

Characteristics:
 Conductor: O.F.C. tinned copper
 Insulation: PVC
 Sheath colours: **Black, White, Red, Green, Blue, Yellow**

| tasker® Code | Cond. number | Nominal section mm² | Nominal section AWG | Cond. Format. mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|---------------------|---------------------|-------------------|-----------------------------|---------------------------|------|-----|
| | | | | | | mt. | Type | Kg. |
| C133 | 1 | 1 x 0,28 | 23 | 1x0,60 (6/10) | 1,2 | 200 | B | 0,9 |

RoHS
Conformity

| Conductor Resistance | Max rated Voltage | Operative Temperature |
|----------------------|-------------------|-----------------------|
| Ω/Km ± 5% | AC - V | °C |
| 70 | 49 | -15 / +70 |

Unipolar flexible cable



Applications:
Unipolar flexible cable for tester and measuring devices.
Conductor composed of n° 64 of Ø mm. 0,10 copper wires.

Characteristics:
 Conductor: O.F.C. tinned copper
 Cond. Insulation: PVC
 Sheath colours: **Black, Red**

| tasker® Code | Cond. number | Nominal section mm² | Nominal section AWG | Cond. Format. mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|---------------------|---------------------|-------------------|-----------------------------|---------------------------|------|-----|
| | | | | | | mt. | Type | Kg. |
| C205 | 1 | 1 x 0,50 | 20 | 64x0,10 | 2,5 | 100 | B | 1,3 |

| Conductor Resistance | Max rated Voltage | Operative Temperature |
|----------------------|-------------------|-----------------------|
| Ω/Km ± 5% | AC - V | °C |
| 45 | 49 | -15 / +70 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Specialised Cables category](#):

Click to view products by [Tasker manufacturer](#):

Other Similar products are found below :

[GP-IE515546DS-002](#) [96CB-L2020PIB2](#) [1200740161](#) [R88ACAKA0015SRE](#) [R88ACAWL005SDE](#) [R88ACRGD0R3C](#) [1300660042](#)
[1300660201](#) [1971465-2](#) [22733-8](#) [2R7004A20F060](#) [SSL009PC2DC012N](#) [FC2A-KC6C](#) [CCSFCBF2](#) [R7ACAB005S](#) [XS2WM12PUR4SA10M](#)
[XS2WM12PVC4SA10M](#) [05AU05](#) [UCABLE](#) [10114734-2010LF](#) [XW2Z010H3](#) [XW2Z010H1](#) [5-1589827-8](#) [5-1589827-4](#) [861084-1](#)
[XW2Z200JB24](#) [5-1589956-8](#) [CR4000A76M020](#) [1201140211](#) [1300140039](#) [CR4000A76M005](#) [CR4006A76M005](#) [10077488-N0550FDLF](#)
[XW2ZRY150C](#) [I4JPBJLUXX100](#) [I4JPBJLUXX50](#) [CM06](#) [CM06W](#) [POE004](#) [0243 009 05](#) [0243 009 20](#) [0243 009 36](#) [0243 009 26](#) [0243 009](#)
[23](#) [0243 009 01](#) [0243 009 30](#) [0243 008 05](#) [0243 008 20](#) [0243 008 36](#) [0243 008 23](#)