



# PJ2301



## 20V P-Channel Enhancement Mode MOSFET

### FEATURES

- $R_{DS(ON)}$ ,  $V_{GS}$  @ -1.8V,  $I_D$  @ -1.5A=200m $\Omega$
- $R_{DS(ON)}$ ,  $V_{GS}$  @ -4.5V,  $I_D$  @ -2.2A=105m $\Omega$
- Advanced Trench Process Technology
- High Density Cell Design For Ultra Low On-Resistance
- Specially Designed for DC/DC converters
- Low gate charge
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. . (Halogen Free)

### MECHANICAL DATA

- Case : SOT-23 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0003 ounces, 0.0084 grams
- Marking : 01



### Maximum Ratings and Thermal Characteristics ( $T_A=25^\circ\text{C}$ unless otherwise noted )

PARAMETER		Symbol	Limit	Units
Drain-Source Voltage		$V_{DS}$	-20	V
Gate-Source Voltage		$V_{GS}$	$\pm 8$	V
Continuous Drain Current (Notes 1)	Steady-State	$I_D$	$T_A=25^\circ\text{C}$	-1.75
	Steady-State		$T_A=70^\circ\text{C}$	-1.4
	$t \leq 5\text{s}$		$T_A=25^\circ\text{C}$	-2
Pulsed Drain Current (Notes 1)		$I_{DM}$	10	A
Power Dissipation (Notes 2)		$P_D$	$T_A=25^\circ\text{C}$	700
			$T_A=70^\circ\text{C}$	450
Typical Thermal Resistance (Notes 1)		$R_{\theta JA}$	175	$^\circ\text{C/W}$
Typical Thermal Resistance (Notes 1)		$R_{\theta JL}$	65	$^\circ\text{C/W}$
Operating Junction and Storage Temperature Range		$T_J, T_{STG}$	-55 to + 150	$^\circ\text{C}$

#### NOTES:

1. Mounted on minimum pad layout.
2. Mounted on 48cm<sup>2</sup> FR-4 PCB board.



# PJ2301


## ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Units
Static						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D = -250\mu A$	-20	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D = -250\mu A$	-0.5	-0.7	-0.9	V
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS} = -4.5V, I_D = -2.2A$	-	90	105	mΩ
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS} = -2.5V, I_D = -1.7A$	-	120	140	
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS} = -1.8V, I_D = -1.5A$	-	170	200	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = -16V, V_{GS}=0V$	-	-	-1	μA
Gate Body Leakage	$I_{GSS}$	$V_{GS} = \pm 8V, V_{DS}=0V$	-	-	±100	nA
Dynamic						
Forward Transconductance	$g_{FS}$	$V_{DS} = -10V, I_D = -1.7A$	4	6	-	S
Total Gate Charge	$Q_g$	$V_{DS} = -10V, I_D = -2.2A$ $V_{GS} = -4.5V$	-	4	-	nC
Gate-Source Charge	$Q_{gs}$		-	0.5	-	
Gate-Drain Charge	$Q_{gd}$		-	1	-	
Turn-On Time	$t_{on}$	$V_{DD} = -16V,$ $I_D = -2.2A, V_{GS} = -4.5V$ $R_{GEN}=2.5\Omega$	-	8	-	ns
Turn-Off Time	$t_{off}$		-	35	-	
Turn-On Rise Time	$t_r$		-	15	-	
Turn-Off Fall Time	$t_f$		-	25	-	
Input Capacitance	$C_{iss}$	$V_{DS} = -10V, V_{GS}=0V$ $f=1.0MHz$	-	200	300	pF
Output Capacitance	$C_{oss}$		-	90	140	
Reverse Transfer Capacitance	$C_{rss}$		-	40	60	
Gate Resistance	$R_g$	$V_{DS}=0V, V_{GS}=0V$ $f=1.0MHz$	-	12	-	Ω
Source-Drain Diode						
Max. Diode Forward Current	$I_s$	-	-	-	-2	A
Diode Forward Voltage	$V_{SD}$	$I_s = -1A, V_{GS}=0V$	-	-0.79	-1	V
Body-Diode Reverse Recovery Time	$t_{rr}$	$I_s = -2.1A, di/dt=100A/\mu s$	-	30	-	ns
Body-Diode Reverse Recovery Charge	$Q_{rr}$		-	12	-	nC




# PJ2301


## CHARACTERISTIC CURVES




**Fig.1 Capacitance Variation**




**Fig.2 On-Region Characteristics**




**Fig.3 Transfer Characteristics**



**Fig.4 On-Resistance vs. Drain Current and Gate Voltage**



**Fig.5 On-Resistance vs. Gate-Source Voltage**



**Fig.6 On-Resistance Variation with Temperature**



# PJ2301

## CHARACTERISTIC CURVES




Fig.7 Gate-to-Source and Drain-to-Source vs. Total Charge




Fig.8 Diode Forward Voltage vs. Current




Fig.9 Resistive Switching Time Variation vs. Gate Resistance




Fig.10 Drain-to-Source Leakage Current vs. Voltage




Fig.11 Thermal Response




# PJ2301

## MOUNTING PAD LAYOUT

SOT-23

Unit : inch(mm)



## ORDER INFORMATION

- Packing information
  - T/R - 12K per 13" plastic Reel
  - T/R - 3K per 7" plastic Reel



# PJ2301


## Part No\_packing code\_Version

PJ2301\_R1\_00001

PJ2301\_R2\_00001

For example :

**RB500V-40\_R2\_00001**



Packing Code <b>XX</b>				Version Code <b>XXXXX</b>		
Packing type	1 <sup>st</sup> Code	Packing size code	2 <sup>nd</sup> Code	HF or RoHS	1 <sup>st</sup> Code	2 <sup>nd</sup> ~5 <sup>th</sup> Code
Tape and Ammunition Box (T/B)	<b>A</b>	N/A	<b>0</b>	<b>HF</b>	<b>0</b>	serial number
Tape and Reel (T/R)	<b>R</b>	7"	<b>1</b>	<b>RoHS</b>	<b>1</b>	serial number
Bulk Packing (B/P)	<b>B</b>	13"	<b>2</b>			
Tube Packing (T/P)	<b>T</b>	26mm	<b>X</b>			
Tape and Reel (Right Oriented) (TRR)	<b>S</b>	52mm	<b>Y</b>			
Tape and Reel (Left Oriented) (TRL)	<b>L</b>	PANASERT T/B CATHODE UP (PBCU)	<b>U</b>			
FORMING	<b>F</b>	PANASERT T/B CATHODE DOWN (PBCD)	<b>D</b>			



## PJ2301

---

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [Panjit](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#) [IRF100S201](#)  
[JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#) [2SK1691-DL-](#)  
[E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#) [424134F](#) [026935X](#)  
[051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#) [IPS70R2K0CEAKMA1](#)  
[RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#) [NTE6400](#) [JANTX2N6796U](#)  
[JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#) [2SK2614\(TE16L1,Q\)](#)