

Coaxial cable 75 Ω MIL. standards



Applications:
Coaxial braided shielded cable for video frequency MIL. C 17 F Standards.

Characteristics:
Conductor: stranded in O.F.C. tinned copper
Insulation: Compact PE
Shield: Braided covering 98% O.F.C. red copper
Sheath: PVC
Sheath colour: Black



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
RG 11 AU	1	1 x 75 Ω (0,88 mm ²)	7x0,40	7,3		10,3	100	B	13,5

Conductor Resistance	Capacity Core/shield	Velocity of propagation			
Ω/Km ± 5%	pF/mt	%			
21	67	66			
Impedance	Voltage	Operative Temperature °C			
Ω ± 3%	V				
75	5000	-15 / +70			
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
4,2	6,2	9,3	13,8	20,5	23,4



Coaxial cable 50 Ω MIL. standards



Applications:
Coaxial braided shielded cable for radio frequency MIL. C 17 F Standards.

Characteristics:
Conductor: stranded in CW
Insulation: Compact PE
Shield: Braided covering 98% O.F.C. tinned copper
Sheath: PVC
Sheath colour: Black



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
RG 174 AU	1	1 x 50 Ω (0,14 mm ²)	7x0,16 CW	1,5		2,8	100 500	B B	1,3 6,8

Conductor Resistance	Capacity Core/shield	Velocity of propagation			
Ω/Km ± 5%	pF/mt	%			
290	100	66			
Impedance	Voltage	Operative Temperature °C			
Ω ± 3%	V				
50	1500	-15 / +70			
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
17,5	25,8	38,2	54,9	77,0	87,5

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coaxial Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[89880-003-1000](#) [633948-877-1000](#) [CY2389-000](#) [8213-010-1000](#) [8221-010-U1000](#) [8233-010-1000](#) [88281-010-500](#) [1322R-010-1000](#) [177799-000](#) [1807A-B59-U1000](#) [9167-010-1000](#) [9251-010-1000](#) [9275-010-U1000](#) [935240-000](#) [9659-010-1000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [144517-000](#) [8-1616396-1](#) [8263-010-U1000](#) [8263 010U500](#) [8268-010-500](#) [8262 010U1000](#) [7915A 009U1000](#) [5024A1311-0](#) [TRC-75-1](#) [1281S5 010250](#) [1281S5 000250](#) [1530A 010U1000](#) [1505A 0081000](#) [9248 010U1000](#) [CO-142BNCX200-001](#) [7809WB 010500](#) [9244 0101000](#) [1694A 0081000](#) [9204 0101000](#) [8241F J5C1000](#) [1530A 0101000](#) [1674A TIN50](#) [7915A 0091000](#) [7915A 010500](#) [TWCH-78-2](#) [TWC-78-1](#)