

September 2018

Multilayer Band Pass Filter

For 5150-5950MHz

DEA165550BT-2230C2-H

1.6x0.8mm [EIA 0603]*

* Dimensions Code JIS[EIA]


Multilayer Band Pass Filter

公TDK

For 5150-5950MHz


DEA165550BT-2230C2-H

SHAPES AND DIMENSIONS



Dimensions in mm

RECOMMENDED LAND PATTERN



Dimensions in mm

O RoHS Directive Compliant Product: See the following for more details related to RoHS Directive compliant products. http://product.tdk.com/en/environment/rohs/

[•] Before using these products, be sure to request the delivery specifications.

ELECTRICAL CHARACTERISTICS

Item	Frequency (MHz)	y Range	Min.	Тур.	Max.
Insertion Loss (dB)	5150 to	5950	—	0.66	0.90
	5150 to	5950	—	_	1.00 (-40 to +85°C)
Return Loss (dB)	5150 to	5950	10	26.8	—
Attenuation (dB)	30 to	2700	35	43	—
	3400 to	3800	30	35	—
	6900 to	7200	10	26	_
	7200 to	7800	15	35	_
	10300 to 1	1700	20	27	—
Power Handling (W)			_	_	1
Characteristic Impedance (Ω)				50 (Nominal)	

• Ta: +25±5°C

_

TEMPERATURE RANGE

Operating temperature	Storage temperature		
(° C)	(°C)		
-40 to +85	-40 to +85		

TERMINATION FINISH


	Material	
-	Ag	

All specifications are subject to change without notice.Before using these products, be sure to request the delivery specifications.


DEA165550BT-2230C2-H


FREQUENCY CHARACTERISTICS

INSERTION LOSS



RETURN LOSS






All specifications are subject to change without notice.Before using these products, be sure to request the delivery specifications.

RF Components

&TDK

DEA165550BT-2230C2-H

RECOMMENDED REFLOW PROFILE



Preheating			Soldering			
Freneating			Critical zone (T3 to T4)		Peak	
Temp.		Time	Temp.	Time	Temp.	Time
T1	T2	t1	Т3	t2	T4	t3*
150°C	200°C	60 to 120sec	217°C	60 to 120sec	240 to 260°C	30sec max.

 * t3 : Time within 5°C of actual peak temperature

The maximum number of reflow is 3.

All specifications are subject to change without notice.Before using these products, be sure to request the delivery specifications.

REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using these products.

⚠ REMINDERS

The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.

Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below or for any other use exceeding the range or conditions set forth in this catalog.

- (1) Aerospace/Aviation equipment
- (2) Transportation equipment (cars, electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment
- (7) Transportation control equipment

- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications

When using this product in general-purpose applications, you are kindly requested to take into consideration securing protection circuit/ equipment or providing backup circuits, etc., to ensure higher safety.

• All specifications are subject to change without notice.

[•] Before using these products, be sure to request the delivery specifications.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Signal Conditioning category:

Click to view products by TDK manufacturer:

Other Similar products are found below :

MAPDCC0004 PD0409J5050S2HF 880157 HHS-109-PIN DC1417J5005AHF DC4859J5005AHF AFS14A30-2185.00-T3 DS-323-PIN DSS-313-PIN B39321R801H210 B39921B4317P810 1A0220-3 2089-6207-00 JP510S LFB212G45SG8C341 LFB322G45SN1A504 LFL182G45TC3B746 SF2159E 30057 1P510S CER0813B 3A325 40287 41180 ATB3225-75032NCT B69842N5807A150 BD0810N50100AHF BD2425J50200AHF HMC189AMS8TR C5060J5003AHF JHS-114-PIN JHS-115-PIN JP503AS DC0710J5005AHF DC2327J5005AHF DC3338J5005AHF 43020 LFB2H2G60BB1C106 LFL15869MTC1B787 X3C19F1-20S XC3500P-20S 10013-20 SF2081E SF2194E SF2238E CDBLB455KCAX39-B0 RF1353C PD0922J5050D2HF 600S150FTRB 1E1305-3