



#### **ADVANTAGE**

Suitable for household appliances

Robust design

Optimized measuring range

High endurance

High signal accuracy

## **PRODUCT FEATURES**

- → Flowmeter for house or drinking water with pulse output
- → Long life paddlewheel design
- → Pulse rate can be optimized for individual flow environment
- → 200 m³
- → Standard accuracy of ± 3 % FS

#### **EXAMPLES OF APPLICATION**


- Washing machines
- → Dishwasher
- > Cleaning equipment
- → Laboratory devices
- → Industrial applications
- Catering appliances


Measuring range	2 – 15 l/min.	
Max. supply voltage	5 V DC	
Max. supply current	5 mA	
Standard output signal	219 pulses/liter	
Tolerance	2 – 4 l/min. ± 5 %, 4 – 15l/min. ± 3 %	
Characteristic pressure drop	< 0.4 bar @10l/min.	
Rupture pressure	8 bar	
Life endurance	200 m³	
Temperature range	+5 °C +70 °C	
Material housing	РОМ	
Terminal type	Hose connectors: 13 mm / 0.5 (inside diameter hose)	

#### **VARIANTS**


Part number	Pulse switch	Terminal type
2061.1201	Reed contact	Rast 2.5


## **FEED LINE**







# INSTALLATION POSITION











# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Marquardt manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160