

**Basic-terminal for Modlight50 assembled with LED-modul green,yellow,red**

Basic, buzzer, flash + LED modules  
green, yellow, red

**Image**

Vicarious picture

<b>Technical Data</b>	
Operating voltage	24 V AC (21.6...26.4 V DC)
Current consumption	max. 62.5 mA
Buzzer (infinitely adjustable)	Continuous and intermittent alarm
Sound pressure level	70 ±5...90 ±5 dB
Blink cycles	60 ±12 per minute
<b>General data</b>	
Protection	IP65 inserted and tightened
Connection	Spring clamp terminals
Housing	Black plastic
Temperature range	-30...+60 °C
Dimensions Ø × H	mm
<b>Commercial data</b>	
Net weight	407
Weight unit	Gram
Basic unit	pc.
Customs tariff number	85439000
Unit (piece)	1
Minimum order quantity (piece)	1

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 12/14

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Lighting Fixtures](#) category:*

*Click to view products by [Murr Elektronik](#) manufacturer:*

Other Similar products are found below :

[1301080067](#) [XVEC21P](#) [XVEC2B7](#) [2701785](#) [2702939](#) [2702476](#) [2702938](#) [2701787](#) [2702941](#) [2701788](#) [2702488](#) [2702491](#) [2702480](#) [2702489](#)  
[2701786](#) [2702484](#) [113163000-00662717](#) [113472000-00691461](#) [LD6A-3DQB-RYG](#) [LD6A-3DZQB-RYG](#) [LF1B-NA3P-2THWW2-3M](#)  
[LF1B-NC3P-2THWW2-3M](#) [LF1B-ND3P-2THWW2-3M](#) [E35600](#) [NB-RLAMP01-LED](#) [FLK7LED](#) [LD6A-3WQB-RYG](#) [XVC4B3K](#)  
[XVBC4M7](#) [2702475](#) [2702482](#) [2702935](#) [2702483](#) [2702936](#) [2702485](#) [2702934](#) [ZWF-638-24CW](#) [ZAF-486-24CW](#) [BC5000-N-S](#) [BP3200-C-](#)  
[S-24](#) [BP3200-C-F-12](#) [BP3100-C-S](#) [BC5000-C-S](#) [2702933](#) [2702477](#) [2403122](#) [2403121](#) [2402991](#) [113261000-00641180](#)  
[113259000-00641174](#)