

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: 470025CY
Page 1 of 2 Pages

Issue: 1
Issue Date: 6/23/2018
Effective Date: 8/18/2018

A. Construction

Diameters (mm)

- | | | |
|-----------------|--|--------------|
| 1) Component 1 | 2 X 1 COND | |
| a) Conductor | 0.5 (20/0.177) mm ² Bare Copper | 0.91 |
| b) Insulation | 0.40 mm Wall, Nom. PVC | 1.71+/- 0.08 |
| (1) Print Color | White | |
| (2) Color Code | Alpha Wire Color Code KZ | |

Cond	Color	Cond	Color	Cond	Color
1	BLACK#1	2	BLACK#2		

- | | | |
|------------------|--|------------------|
| c) Cabling | 2 COND Bunch Cabled | 3.42 |
| (1) Max Lay: | 70 mm LH Lay | |
| (2) Layup: | 2 | |
| (3) Orientation: | Components to be arranged from INSIDE LAYER to OUTSIDE LAYER | |
| d) Jacket | 0.65 mm Wall, Nom., PVC | 4.76+/-0.20 |
| (1) Color(s) | GREY | |
| 2) Shield | Tinned Copper BRAID Shield, 80% Coverage, Min. | |
| 3) Jacket | 0.80 mm Wall Nom., PVC | 7.10 (7.35 Max.) |
| a) Color(s) | GREY (RAL-7001), CLEAR | |
| b) Print | ALPHA WIRE-* P/N 470025CY
PRO-MET 300/500V 2X0.5MM2 PVC/PVC/TCB/PVC MULTI CORE
CONTROL CABLE ◁ VDE-REG 8770 ▷ CE ROHS
DDDYANN XXXXXXX M | |

* = Factory Code

B. Applicable Specifications

- | | |
|----------------|--|
| 1) IEC | |
| a) Component 1 | EN 60228 Conductors, Class 5
DIN VDE 0295 Class 5 |
| 2) Other | IEC 60332-1 Flame Behavior
DIN EN 50290-2-22 Oil Resistance
UV Resistant |
| 3) CE: | EU Low Voltage Directive 2014/35/EU |

C. Environmental Compliance

- | | |
|-------------------------------------|--|
| 1) CE: | EU Directive 2011/65/EU(RoHS2):
All materials used in the manufacture and packaging of this part must meet the requirements of European Directive 2011/65/EU and the amending Directive 2015/863/EU of 4 June 2015 regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. |
| 2) REACH Regulation (EC 1907/2006): | This product may not contain any of the substances listed in the latest issue European Union's REACH Substance of Very High Concern (SVHC) candidate list in excess of 0.1% mass of the item. |

D. Physical & Mechanical Properties

- | | |
|------------------------|--|
| 1) Temperature Range | -40 to 80°C(static), -30 to 70°C (dynamic) |
| 2) Bend Radius | 6X Cable Diameter(static), 20X Cable Diameter(dynamic) |
| 3) Sunlight Resistance | Yes |

E. Electrical Properties

- | | |
|-------------------|---|
| 1) Voltage Rating | (For Engineering purposes only)
300/500 V _{RMS} |
|-------------------|---|

This specification outlines the requirements for the product(s) described herein. Deviations from this specification are not permitted without the written authorization of the Alpha Wire Engineering Department. All finished products will be inspected to the specification and noncompliance or unauthorized deviations will be cause for rejection and return of product.
If vendor certifying agency requirements are in conflict with this document, it is incumbent upon the vendor to notify the Alpha Wire Engineering Department and mark up differences on this document and submit them for review and approval prior to any production. Be advised that product legend information and product label information and product label information must be in concert; both are the responsibility of the vendor.
It is the responsibility of the vendor to insure that this product meets the requirements of subservient certifying agency documents even though they are not directly noted herein.
All information contained herein is confidential. Its use is restricted to authorized Alpha Wire Company personnel or authorized vendors of the Alpha Wire Company. Under no circumstances shall this document be duplicated in any form or shown to/discussed with unauthorized personnel without the expressed written consent of the Alpha Wire Engineering Department.

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: 470025CY
Page 2 of 2 Pages

Issue: 1
Issue Date: 6/23/2018
Effective Date: 8/18/2018

2) Conductor DCR 39 Ω /Km @20°C, Max.

F. Other

1) Packaging Flange x Traverse x Barrel (inches)
a) 300 M 16 x 11 x 8 Continuous length
b) 100 M 12 x 4.5 x 3.5 Continuous length
c) 50 M 12 x 4.5 x 3.5 Continuous length
[Spool dimensions may vary slightly]

This specification outlines the requirements for the product(s) described herein. Deviations from this specification are not permitted without the written authorization of the Alpha Wire Engineering Department. All finished products will be inspected to the specification and noncompliance or unauthorized deviations will be cause for rejection and return of product. If vendor certifying agency requirements are in conflict with this document, **it is incumbent upon the vendor to notify the Alpha Wire Engineering Department** and mark up differences on this document and submit them for **review and approval prior to any production**. Be advised that **product legend information and product legend information and product label information must be in concert**; both are the responsibility of the vendor. It is the **responsibility of the vendor** to insure that this product meets the requirements of subservient certifying agency documents even though they are not directly noted herein. All information contained herein is confidential. Its use is restricted to authorized Alpha Wire Company personnel or authorized vendors of the Alpha Wire Company. Under no circumstances shall this document be duplicated in any form or shown to/discussed with unauthorized personnel without the expressed written consent of the Alpha Wire Engineering Department.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Alpha manufacturer](#):

Other Similar products are found below :

[89504-002-1000](#) [89705-008-500](#) [6120UL-002-1000](#) [CS2885-000](#) [M27500-20SP2S23](#) [6300FE-877-U1000](#) [6309UE-877-1000](#) [M3905-BK005](#)
[6502FE 8771000](#) [6541PA-008-U1000](#) [CV6807-000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-](#)
[0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [752687-000](#) [768146-000](#) [773159-000](#)
[82841-877-5000](#) [83318E-009-500](#) [8348-060-500](#) [8404-060-500](#) [8469 060100](#) [858171-000](#) [8628-060-500](#) [868361-001](#) [8730-060-1000](#) [8737-](#)
[060-U1000](#) [8747-060-100](#) [8747-060-1000](#) [8769-060-1000](#) [8775-060-500](#) [87760-002-5000](#) [8780-060-1000](#) [8782-001-U1000](#) [9159-060-500](#)
[9318-060-1000](#) [939870-000](#) [9423 060U500](#) [9444 060U1000](#) [9497 0001000](#) [9515-060-1000](#) [9524-060-1000](#) [9539-060-5000](#) [9546-060-500](#)