

## KONTAKT 60 PLUS



### Description:

Kontakt 60 Plus is specially designed for the cleaning and protection of electrical and electro-mechanical parts.

### General properties and applications:

The solvents penetrate in the most difficult to reach areas. The special components will remove persistent corrosion and deposits (oxides, sulphides,..) from all kinds of metal contacts, improving the electrical conductivity. The protective film will reduce the friction and wear and will protect the contacts from severe corrosive atmospheric influences. Kontakt 60 Plus is used for maintenance and repair jobs on TV, radio, electronic equipment household appliances, (car) electronics,.....

Kontakt 60 Plus is safe to use on metals, graphite, carbon-elements. Safe on most plastics and insulators (in case of doubt, test prior to use).

NSF registration : K2 (registration number : 140308)

### Technical data (after evaporation of solvents)

Density (@ 20 °C)	ASTM D891	0,75 g/cm <sup>3</sup>
Flash point	ASTM D56	< 0 °C
color		amber

### Corrosion Humidity Cabinet according to ASTM D 1748



Non treated steel plate.  
 After 20 hours of exposure.



Treated with Kontakt 60 Plus.  
 After 820 hours of exposure.



**Application instructions:**

Never use on energized equipment. Shake can well before usage. Spray onto the contact surfaces and allow acting. After drying, if necessary, remove dirt with a cloth or blow it away with Dust Off. Then spray a final film. Move the contacts. Allow to dry.

When applying the product, ensure there is good ventilation. Kontakt 60 Plus contains highly flammable isopropanol.

***A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all KONTAKT CHEMIE products.***

**Available:**

Aerosol, 200 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 20739 03 0308 00

Date : 17 March 2008

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Chemicals](#) category:*

*Click to view products by [Kontakt Chemie](#) manufacturer:*

Other Similar products are found below :

[HANDPAD](#) [1624-10S](#) [3045-QT](#) [3065-15S](#) [3125-9S](#) [5200-WHITE-3OZ](#) [70008073302](#) [1398159-1](#) [S1255-04-34X100FT](#) [3748-Q-58"x8"](#) [FO-25DT](#) [13844](#) [S1009-KIT-A-CS8606](#) [8361-P](#) [2216-GRAY-2OZ](#) [DP100-200ML](#) [1743-2FP](#) [2310-10](#) [VERSIL406](#) [826-450G](#) [SS4120-1P](#) [3789-Q](#) [9729](#) [9223](#) [9176](#) [600-0510](#) [3748PG](#) [04952-00531-00](#) [04952-00533-00](#) [10-50L](#) [3748-Q-5/8"X8"](#) [3764-TC](#) [3M 9087](#) [3M 9088](#) [AS1700](#) [120-320](#) [BLR-15ML](#) [HYBRICX 35C](#) [7552](#) [7558](#) [3748-V-O-Q-5/8"X8"](#) [3764-Q](#) [3779-TC](#) [3797TC](#) [3M 9086](#) [100500F00000G](#) [101800F00000G](#) [1610-5G](#) [1610-G4](#) [1621-5G](#)