

## 1. GENERAL DESCRIPTION

---

Pure Vaseline spray used as lubricant and anti-corrosion product.

## 2. FEATURES

---

KONTAKT 701 contains pure, white, pasty Vaseline (paraffin oil which hardens to a pasty consistency at room temperature). The product combines the excellent lubricating and anti-corrosion properties of Vaseline with the easy use of an aerosol can : clean and firm handling and storage, mobile and easy, precise dosage.

KONTAKT 701 is compatible with most materials including metal, rubber, wood, leather and synthetics and elastomers that are resistant to paraffin oil (not polycarbonate, polystyrene and EPDM).

## 3. APPLICATIONS

---

KONTAKT 701, as lubricant and anti-corrosion product, is used for example in the radio- and electro technology as in the antenna assembly. Screw and clamp connectors are being sealed and protected by KONTAKT 701. Lubricates slides reliably.

## 4. DIRECTIONS

---

- Using the extension tube, KONTAKT 701 as a spray can be dosed accurately. The aerosol can be used in an up-side-down position (360° valve), so hard to reach parts can also be treated. Shake can before use.
- KONTAKT 701 when used as a protective coating against corrosion, should be applied in relative thick layers. Screw and clamp contacts should be given a coating of approx. 1 mm. As a lubricant although, only a thin film is required.
- Many materials, including synthetics, tolerate KONTAKT 701 quite well. For series production runs however, a compatibility test should always be carried out. With most elastomers a slight swelling is not critical, provided precise dimensional stability is not required. KONTAKT 701 is unsuitable for example as a lubricant for polystyrene, polycarbonate and EPDM rubbers.
- KONTAKT 701 spray contains flammable solvents. Don't use the product on energised equipment. Wait until all solvents evaporated before switching on equipment (minimum 15 min.).
- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.

**5. TYPICAL PRODUCT DATA (without propellant)**

---

**Aerosol**

Density at 20°C	:	0,72 g/cm <sup>3</sup>
Flash point	:	<0°C

**Active agent**

Aspect	:	white, creamy
Density at 20°C	:	0,72
Congelation point	:	ca. 50°C

**6. PACKAGING**

---

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 20835 03 1003 03  
Date : 10 June 2011



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Chemicals](#) category:*

*Click to view products by [Kontakt Chemie](#) manufacturer:*

Other Similar products are found below :

[HANDPAD](#) [1624-10S](#) [3045-QT](#) [3065-15S](#) [3125-9S](#) [5200-WHITE-3OZ](#) [70008073302](#) [1398159-1](#) [S1255-04-34X100FT](#) [3748-Q-58"x8"](#) [FO-25DT](#) [13844](#) [S1009-KIT-A-CS8606](#) [8361-P](#) [2216-GRAY-2OZ](#) [DP100-200ML](#) [1743-2FP](#) [2310-10](#) [VERSIL406](#) [826-450G](#) [SS4120-1P](#) [3789-Q](#) [9729](#) [9223](#) [9176](#) [600-0510](#) [3748PG](#) [04952-00531-00](#) [04952-00533-00](#) [10-50L](#) [3748-Q-5/8"X8"](#) [3764-TC](#) [3M 9087](#) [3M 9088](#) [AS1700](#) [120-320](#) [BLR-15ML](#) [HYBRICX 35C](#) [7552](#) [7558](#) [3748-V-O-Q-5/8"X8"](#) [3764-Q](#) [3779-TC](#) [3797TC](#) [3M 9086](#) [100500F00000G](#) [101800F00000G](#) [1610-5G](#) [1610-G4](#) [1621-5G](#)