Yuasa Technical Data Sheet

Yuasa RE5-12 Industrial VRLA Battery

Specifications

Nominal voltage (V)

20-hr rate Capacity to 10.5V at 20°C (Ah)

10-hr rate Capacity to 10.8V at 20°C (Ah)

4.6

Dimensions

 Length (mm)
 $90 (\pm 0.5)$

 Width (mm)
 $70 (\pm 0.5)$

 Height (mm)
 $102 (\pm 0.5)$

 Height over terminals (mm)
 $106 (\pm 0.5)$

 Mass (kg)
 1.96

Terminal Type

FASTON - Quickfit / release (IST where stated) 6.35

Operating Temperature Range

Storage (in fully charged condition) -15°C to $+45^{\circ}\text{C}$ Charge -15°C to $+45^{\circ}\text{C}$ Discharge -15°C to $+45^{\circ}\text{C}$

Storage

Capacity loss per month at 20°C (% approx.)

Case Material

Standard ABS (UL94:HB) FR version available UL94:V0

Charge Voltage

Float charge voltage at 20°C (V)/Block 13.65 (\pm 1%) Float charge voltage at 20°C (V)/Cell 2.275 (\pm 1%)

Float Chg voltage tmp correction factor from std -3

20°C (mV)

Cyclic (or Boost) charge Voltage at 20° C (V)/Block 14.5 ($\pm 3\%$) Cyclic (or Boost) charge Voltage at 20° C (V)/Cell 2.42 ($\pm 3\%$) Cyclic Chg voltage tmp correction factor from std -4

20°C (mV)

Charge Current

Float charge current limit (A) No limit
Cyclic (or Boost) charge current limit (A) 1.25

Maximum Discharge Current

1 second (A) 120 1 minute (A) 40

Impedance

Measured at 1 kHz ($m\Omega$) 42


Design Life & Approvals

EUROBAT Classification: General Purpose 6 to 9 Yuasa design life at 20°C (yrs) up to 10





Layout



3rd Party Certifications

ISO9001 - Quality Management Systems UNDERWRITERS LABORATORIES Inc.





Safety

Installation

Can be installed and operated in any orientation except permanently inverted.

Handles

Batteries must not be suspended by their handles (where fitted).

Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.


Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.











X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sealed Lead Acid Battery category:

Click to view products by Yuasa manufacturer:

Other Similar products are found below:

1109004 0809-0012 0819-0012 0850-0004 0859-0012 0800-0004 LC-R0612P PS-1250F1 APCRBC123 APCRBC124 LCRA1212P NP1212 NP12-6 NP3.2-12 LC-P0612P LC-R063R4P LC-R067R2P1 LC-R121R3P LC-R0612P1 LC-R127R2P1 LC-X1220AP UP-VW1245P1
2320296 2320306 2320319 2320322 2320335 2320416 2320429 2908237 RBC32 RBC11A RBC36-SLT