

Infrared Thermometer

Professional gun type 8861/8866



- ▲ THE MOST PROFESSIONAL CHOICE
- ▲ QUICK RESPONSE: 500ms
- ▲ BACKLIGHT FUNCTION SELECTABLE
- ▲ TEMP. UNIT C/F IS SWITCHABLE
- ▲ AUTO POWER OFF
- ▲ 9 POINTS MEMORY RECALL
- ▲ D:S RATIO IS 10:1
- ▲ POWERED BY 9 VOLT BATTERY



Model	8861	8866
Temp. range	-20~420°C	-20~420°C
Temp. resolution	1°C/°F	1°C/°F
Temp. accuracy (Which is greater)	+/-2.5% or 2°C (whichever is greater) at 18~28°C operation temperature	+/-2.5% or 2°C (whichever is greater) at 18~28°C operation temperature
Repeatability	+/-1°C	+/-1°C
Emissivity	0.95	0.3~1.0 Adjustable
D:S ratio	10:1	10:1
LCD size	19(H)x34(W)mm	
Operating temp.	10~40°C	
Operating RH%	Humidity < 80%	
Storage temp.	-20~50°C	
Storage RH%	Humidity < 90%	
Dimension	208x116x49 mm	
Laser sighting	NO	Yes
MAX/MIN/ΔT/AVG	NO	Yes
HI/LOW audible alarm	NO	Yes
9 points memory	Yes	Yes
Weight	240g	
Battery	9V battery x 1pc	
Battery Life	100hours	
Standard Package	Meter/Battery/Manual/Hard carry case	



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [AZ Displays](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)