


NPN SILICON POWER SWITCHING TRANSISTORS

BC140, BC141



**TO-39
Metal Can Package**

Medium Power Amplifier and Switching Applications

Complementary BC160 and BC161

ABSOLUTE MAXIMUM RATINGS

| DESCRIPTION | SYMBOL | BC140 | BC141 | UNITS |
|--|----------------|--------------|-------|---------------------------|
| Collector Emitter Voltage | V_{CEO} | 40 | 60 | V |
| Collector Base Voltage | V_{CBO} | 80 | 100 | V |
| Emitter Base Voltage | V_{EBO} | 7.0 | | V |
| Collector Current - Continuous | I_C | 1.0 | | A |
| Power Dissipation@ $T_a=25^\circ\text{C}$ Derate Above 25°C | P_D | 0.8 4.57 | | W mW/ $^\circ\text{C}$ |
| Power Dissipation@ $T_c=25^\circ\text{C}$ Derate Above 25°C | P_D | 4.0 22.73 | | W mW/ $^\circ\text{C}$ |
| Operating and Storage Junction Temperature Range | T_j, T_{stg} | - 65 to +200 | | $^\circ\text{C}$ |

THERMAL CHARACTERISTICS

| | | | |
|---------------------------------|---------------|-----|--------------------|
| Junction to Ambient in free air | $R_{th(j-a)}$ | 219 | $^\circ\text{C/W}$ |
| Junction to Case | $R_{th(j-c)}$ | 44 | $^\circ\text{C/W}$ |


ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless specified otherwise)

| DESCRIPTION | SYMBOL | TEST CONDITION | MIN | TYP | MAX | UNITS |
|---------------------------|------------|---|-----------------------|----------------------|--------------------------|---------------------|
| Collector Emitter Voltage | V_{CES} | $I_C=100\mu\text{A}, V_{BE}=0$ BC140 BC141 | 80 100 | | | V V |
| Collector Emitter Voltage | $*V_{CEO}$ | $I_C=30\text{mA}, I_B=0$ BC140 BC141 | 40 60 | | | V V |
| Emitter Base Voltage | V_{EBO} | $I_E=100\mu\text{A}, I_C=0$ | 7 | | | V |
| Collector Cut off Current | I_{CES} | $V_{CE}=60\text{V}, V_{BE}=0$ $V_{CE}=60\text{V}, V_{BE}=0, T_a=150^\circ\text{C}$ | | | 100 100 | nA μA |
| DC Current Gain | $*h_{FE}$ | $I_C=100\text{mA}, V_{CE}=1\text{V}$ BC140 / BC141 Group-6 Group-10 Group-16 $I_C=1\text{A}, V_{CE}=1\text{V}$ BC140 / BC141 Group-6 Group-10 Group-16 | 40 40 63 100 | | 400 100 160 250 | |
| | | | | 26 15 20 30 | | |

*Pulsed: Pulse duration $\leq 300\text{ms}$, Duty cycle $\leq 1\%$

NPN SILICON POWER SWITCHING TRANSISTORS

BC140, BC141



TO-39
Metal Can Package

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless specified otherwise)

| DESCRIPTION | SYMBOL | TEST CONDITION | MIN | TYP | MAX | UNITS |
|--------------------------------------|----------------|-----------------------------------|-----|-----|-----|-------|
| Collector Emitter Saturation Voltage | $*V_{CE(sat)}$ | $I_C=1\text{A}, I_B=0.1\text{A}$ | | | 1.0 | V |
| Base Emitter on Voltage | $*V_{BE(on)}$ | $I_C=1\text{A}, V_{CE}=1\text{V}$ | | | 2.0 | V |

DYNAMIC CHARACTERISTICS


| | | | | | | |
|----------------------|----------|--|----|--|----|-----|
| Transition Frequency | f_T | $I_C=50\text{mA}, V_{CE}=10\text{V}, f=20\text{MHz}$ | 50 | | | MHz |
| Output Capacitance | C_{ob} | $V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$ | | | 25 | pF |
| Input Capacitance | C_{ib} | $V_{EB}=0.5\text{V}, I_C=0, f=1\text{MHz}$ | | | 80 | pF |

SWITCHING CHARACTERISTICS

| | | | | | | |
|---------------|-----------|--|--|--|-----|----|
| Turn on time | t_{on} | $I_C=150\text{mA}, I_{B1}=7.5\text{mA}$ | | | 250 | ns |
| Turn off time | t_{off} | $I_C=150\text{mA}, I_{B1}=I_{B2}=7.5\text{mA}$ | | | 850 | ns |



*Pulsed: Pulse duration $\leq 300\text{ms}$, Duty cycle $\leq 1\%$

TO-39 Metal Can Package



| DIM | MIN | MAX |
|-----|--------|--------|
| A | 8.50 | 9.39 |
| B | 7.74 | 8.50 |
| C | 6.09 | 6.60 |
| D | 0.40 | 0.53 |
| E | — | 0.88 |
| F | 2.41 | 2.66 |
| G | 4.82 | 5.33 |
| H | 0.71 | 0.86 |
| J | 0.73 | 1.02 |
| K | 12.70 | — |
| L | 42 DEG | 48 DEG |

All dimensions are in mm



PIN CONFIGURATION

- 1. EMITTER
- 2. BASE
- 3. COLLECTOR

Packing Details

| PACKAGE | STANDARD PACK | | INNER CARTON BOX | | OUTER CARTON BOX | | |
|---------|-----------------|----------------|------------------|-----|-------------------|-----|--------|
| | Details | Net Weight/Qty | Size | Qty | Size | Qty | Gr Wt |
| TO-39 | 500 pcs/polybag | 540 gm/500 pcs | 3" x 7.5" x 7.5" | 20K | 17" x 15" x 13.5" | 32K | 40 kgs |

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-2579 6150 Fax + 91-11-2579 9569, 2579 5290
e-mail sales@cdil.com www.cdil.com www.cdilsemi.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [CDIL manufacturer](#):

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [MJ15024/WS](#) [MJ15025/WS](#) [BC546/116](#) [BC556/FSC](#) [BC557/116](#) [BSW67A](#) [HN7G01FU-A\(T5L,F,T](#)
[NJVMJD148T4G](#) [NSVMMBT6520LT1G](#) [NTE187A](#) [NTE195A](#) [NTE2302](#) [NTE2330](#) [NTE2353](#) [NTE316](#) [IMX9T110](#) [NTE63](#) [NTE65](#)
[C4460](#) [SBC846BLT3G](#) [2SA1419T-TD-H](#) [2SA1721-O\(TE85L,F\)](#) [2SA1727TLP](#) [2SA2126-E](#) [2SB1202T-TL-E](#) [2SB1204S-TL-E](#) [2SC5488A-](#)
[TL-H](#) [2SD2150T100R](#) [SP000011176](#) [FMC5AT148](#) [2N2369ADCSM](#) [2SB1202S-TL-E](#) [2SC2412KT146S](#) [2SC4618TLN](#) [2SC5490A-TL-H](#)
[2SD1816S-TL-E](#) [2SD1816T-TL-E](#) [CMXT2207 TR](#) [CPH6501-TL-E](#) [MCH4021-TL-E](#) [BC557B](#) [TTC012\(Q\)](#) [BULD128DT4](#) [JANTX2N3810](#)
[Jantx2N5416](#) [US6T6TR](#) [KSF350](#) [068071B](#)