

UNITRONIC® BUS CC FD P FRNC

CC-Link bus cable for high flexible applications - UL-verified

CC-Link to provide efficient, integrated factory and process automation. UV-resistant, flame retardant. AWM style 300V. Temperature range from -40°C bis +80°C

Info

Lapp Kabel is a regular member of the user organisation CC-Link Partner Association (CLPA), Japan.



Power chain



Oil-resistant



Halogen-free



Mechanical and plant engineering



Kompletterande automationskomponenter från Lapp

Benefits

The CC-Link® system was developed by Mitsubishi Electric Automation, Japan.

Application range

CC-Link® (Control & Communication Link) = field bus network, for both control as well as information data to provide efficient, integrated factory and process automation.

For highly flexible applications (power chains, moving machine parts)

UNITRONIC® BUS CC FD P FRNC

Product features

Transmission rate in relation to the distance
156 kbit/s 1.200 m
625 kbit/s 600 m
2,5 Mbit/s 200 m
5,0 Mbit/s 110-150 m
10 Mbit/s 50-100 m
Halogen-free
Flame-retardant according IEC 60332-1-2

Norm references / Approvals

AWM 20233 80 °C 300V

Product Make-up

Bare stranded copper wires
Core insulation: PE
Inner sheath: FRNC
Overall screening of braided tinned-copper strands
Outer sheath: PUR, red (RAL 3000)

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000830 ETIM 5.0 Class-Description: Data cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000830 ETIM 6.0 Class-Description: Data cable
Certifications:	UL AWM Style 20233
Peak operating voltage:	300 V
Conductor resistance:	11 ohm/1,000 ft. (305 m) at 20 °C
Minimum bending radius:	Fixed installation: 4 x outer diameter Moved: 10 x outer diameter
Test voltage:	2000 V
Characteristic impedance:	110 ohm at 1 MHz
Temperature range:	-40 °C to +80 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

CC-Link® is a registered trademark of CC-Link Partner Association, Japan (CLPA)

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Article designation	Number of cores and AWG size	Outer diameter [mm]	Copper index (kg/km)
2170370	UNITRONIC® BUS CC FD P FRNC	3 x 1 x AWG20	8.5	39.9

Last Update (20.10.2018)
 ©2018 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03.16

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[0152660053](#) [603020002](#) [73-7797-25](#) [73-8890-10](#) [73-8890-14](#) [73-8891-14](#) [73-8891-25](#) [73-8892-50](#) [73-8894-10](#) [73-8894-3](#) [73-8895-14](#) [73-8896-7](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [9QA0-111-12-3.00](#) [1200650742](#) [1200700174](#) [1200860368](#) [1200650013](#) [1201080008](#) [1-21919-1](#) [1300500373](#) [1300101844](#) [1300101845](#) [130050-0004](#) [1300500014](#) [1410147](#) [E16A06002M030](#) [E200102-009-S1](#) [MT14-187L](#) [17-103530](#) [NK5EPC18RDY](#) [NK5EPC18VLY](#) [NK5EPC18YLY](#) [NK5EPC1GRY](#) [NK5EPC30BLY](#) [NK5EPC30VLY](#) [NK5EPC30YLY](#) [NK5EPC4Y](#) [NK5EPC6YLY](#) [NK5EPC8BLY](#) [NK5EPC9YLY](#) [NK6PC30BUY](#) [NK6PC30GRY](#) [NK6PC30RDY](#) [NK6PC30Y](#) [NK6PC30YLY](#) [1969343-6](#) [C501100010](#) [C501106002](#)