

# C.A 1246

## Logger Thermo-Hygrometer



### Measure humidity and temperature in all conditions

- Compact and magnetized for fixed or portable use
- Recording up to 1 million points
- Alarms and recording trigger on alarm
- Battery life of up to 3 years
- IP54 casing



Data Logger Transfer  
Automatic report generation



Bluetooth<sup>®</sup>

Measure up



12 °C

## C.A 1246 Logger Thermo-Hygrometer

### RELATIVE HUMIDITY

Type	Capacitive sensor	
Measurement range	3.0 to 98.0 %RH	
Resolution	0.1 %RH	
Intrinsic uncertainty	10 to 90 %RH: $\pm (2 \%RH \pm 1 \text{ ct})$ , outside that range: $\pm (4 \%RH \pm 1 \text{ ct})$	
Response time (66%)	60 s	

### TEMPERATURE

Type of sensor	Temperature sensor with semiconductor	
Measurement range	- 10.0 to + 60.0°C	14.0 to + 140.0°F
Resolution	Display in °C: 0.1°C	Display in °F: 0.1°F
Intrinsic uncertainty in °C	10 to 40°C: $\pm (0.5^\circ\text{C} \pm 1 \text{ ct})$ outside that range: $\pm (0.032 \times (T-25) \pm 1 \text{ ct})$ / T= temperature in °C	
Response time (66%)	30 s	

### DEW POINT

Measurement range	- 20.0 to + 60.0°Ctd	-4.0 to + 140.0 °Ftd
Resolution	Display in °C: 0.1°C	Display in °F: 0.1°F

### FUNCTIONS

Recording	<b>Manual Start / Stop on the product</b> short press for MEM spot recording / Long press for REC recording at the rate of the current mode <b>Programmed recording:</b> start date, recording interval (1 minute to 2 hours) and end date defined using the PC software
Alarms	Alarm thresholds settable in the software / Recording can be triggered on an alarm threshold
Data storage	More than 1 million points
Min-Max-Hold	Yes
Units	°C or °F / %RH
Backlighting	Yes
Automatic power-off	Yes (configurable)

### POWER SUPPLY

Type	3 x 1.5V AA / LR6 alkaline batteries Connection to the mains possible with the mains / micro-USB adapter offered as an accessory
Battery life	1,000 hrs (portable mode) / 3 years of recording (15-minute measurement interval)

### PHYSICAL SPECIFICATIONS

Interfaces	2 possible communication modes: Bluetooth wireless link and USB
Mounting	Casing equipped with a magnet, a wall-mount system and a slot for suspending the product Compatible with the Multifix accessory
Dimensions / weight	187 x 72 x 32 mm / 260 g with batteries
Ingress protection	IP54 casing
Product operating range	Temperature: -10 to +60 ° C / Humidity: 10 to 90 %RH
Compliance	IEC61010-1 / IEC 61326-1

### GENERAL SPECIFICATIONS

Data Logger Transfer Windows PC software functions	Display as a graph or a table of values / Data export in graph or Excel table form Real-time mode / Automatic report generation in Word format / Data format compatible with the Dataview software offered as an accessory
Warranty	2 years

### Accessories / Replacement parts

75%RH salt cartridge .....	P01156401
33%RH salt cartridge .....	P01156402
Shockproof sheath + Multifix .....	P01654252
Multifix .....	P01102100Z
Mains adapter .....	P01651023
Bag .....	P01298075
Metal case .....	P01298071
Dataview software .....	P01102095
Bluetooth BLE / USB modem for PC .....	P01654253
4 x AA/LR6 NiMH Batteries + Battery charger .....	HX0053

### Standard state at delivery:

**Bag, 3x1.5V AA batteries, USB cable, test report and quick start-up guide** (complete manual and Data Logger Transfer software available on the Chauvin Arnoux website)



TO ORDER

**C.A 1246 Logger thermo-hygrometer**  
..... P01654246

**FRANCE**  
**Chauvin Arnoux**  
190, rue Championnet  
75876 PARIS Cedex 18  
Tél : +33 1 44 85 44 85  
Fax : +33 1 46 27 73 89  
info@chauvin-arnoux.fr  
www.chauvin-arnoux.fr

**UNITED KINGDOM**  
**Chauvin Arnoux LTD**  
Unit 1 Nelson Ct, Flagship Sq, Shaw Cross Business Pk  
Dewsbury, West Yorkshire - WF12 7TH  
Tel: +44 1924 460 494  
Fax: +44 1924 455 328  
info@chauvin-arnoux.co.uk  
www.chauvin-arnoux.com

**MIDDLE EAST**  
**Chauvin Arnoux Middle East**  
P.O. BOX 60-154  
1241 2020 JAL EL DIB - LEBANON  
Tel: +961 1 890 425  
Fax: +961 1 890 424  
camie@chauvin-arnoux.com  
www.chauvin-arnoux.com

 **CHAUVIN  
ARNOUX**  
GROUP

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Environmental Test Equipment](#) category:*

*Click to view products by [Chauvin Arnoux](#) manufacturer:*

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)  
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)  
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)  
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)