

PCB Mount Miniature Speakers



- PCB mounting
- 1200 Hz frequency

Designed to satisfy the need for a small, PCB mountable speaker transducer for use in keyboards. It has a low profile and a sound output suitable for an office-type environment.

Mfrs. List No.	AST-030COMR-R
Rated Input Power	0.15W
Maximum Input Power	0.3W
Impedance	100Ω ± 20%
Sound Pressure Level	80dB
Resonant Frequency	1200Hz ± 10%
Frequency Range	1200Hz to 10000Hz
Operating Temperature	-20°C to +60°C
Dimensions	∅29.7mm x 12.7mm
Weight	8.5g
Pin Pitch x Pin Dia.	15.0 x ∅1.0mm

338904.473091

Mfrs. List No.	Order Code	Price Each
AST-030COMR-R	119-2971 ●	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Projects Unlimited](#) manufacturer:

Other Similar products are found below :

[AW-15SBW](#) [AOM-4546L-R](#) [AI-383](#) [AT-1438-TWT-R](#) [AI-4328-P-FP250-R](#) [AI-4329-P-FP28-R](#) [X-4032-TF-LW105-R](#) [X-4035-TFL-LW140-R](#) [POM-5242P-R](#) [AOM-4540L-R](#) [X-2629-TWT-R](#) [AT-2440-TWT-R](#) [AT-1620-TWT-12V-R](#) [SMI-1324-TW-5V-2-R](#) [AST-03032MR-R](#) [POM-1644P-NF-R](#) [AI-550](#) [AOM-6738P-R](#) [AS01308MR-LW10](#) [AST-030C0MR-R](#) [AI-4328-P-C28-2-R](#) [TOM-1545P-R](#) [POM-3044P-R](#) [SMT-0727-S-R](#) [AOM-6738L-R](#) [AT-1220-TWT-5V-R](#) [AOM-4540P-R](#) [ROM-2238P-NF-R](#) [AI-1440-TWT-12V-R](#) [AT-1620-TWT-R](#)