


A range of leads featuring high quality, low noise Gotham microphone cable. The double lap screened cable is ideally suited to studio applications due to its construction, each lap screen being wound in opposite directions. This feature provides unsurpassed noise rejection yet still maintains a high degree of flexibility.

3 way Free Plug as per
 Product Specification 701-709-705-713
 3 way Free Socket as per
 Product Specification 700-708-704-712
 Cable GAC-2 as per
 Product Specification 439 Series

Dimensions



NICKEL	BLACK	LENGTH
730-0010	731-0010	1.0m
730-0030	731-0030	3.0m
730-0050	731-0050	5.0m
730-0100	731-0100	10.0m

CONVERTED FROM PS0441 ISS6 (16.02.96) IN JAN 2003

Drgn No 730-731

TITLE PROFESSIONAL QUALITY MICROPHONE LEADS

ALL DIMENSIONS IN MM
 ANGLES IN DECIMAL DEGREES



DELTRON Components

ESTD 1955

6

GENERAL SPECIFICATION
 FOR 730-731

CUSTOMER

FILTER REF

Aprvd Date 16.02.96

Aprvd By

MC

Drwn by

BFS

Scale: NTS

Sheet 1 / 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Deltron](#) manufacturer:

Other Similar products are found below :

[575-0101](#) [571-0200](#) [334-0000](#) [342-0000](#) [W127G](#) [459-0070](#) [066541F](#) [066542D](#) [W205C](#) [W106C](#) [717-0400](#) [4MP1308](#) [000-035-100](#) [461-0010](#) [486-121209-66](#) [490-170805E-68](#) [490-250805E-68](#) [577-0500](#) [557-0500](#) [486-261612-66](#) [486-121208-68](#) [480-0050](#) [456-0100](#) [486-261612-68](#) [4DR3526](#) [590-0400](#) [486-261612](#) [483-0100](#) [461-0020E](#) [459-0110](#) [479-0020-5](#) [356-0200](#) [480-C060](#) [331-0000](#) [459-0080](#) [462-0020E](#) [4MP2616](#) [460-0090](#) [455-0060](#) [480-0040](#) [480-0030](#) [490-040503A-68](#) [800-0400](#) [MDU14S](#) [487-261612E-66](#) [483-0030](#) [480-0010](#) [466-0150](#) [455-0020](#) [455-0010](#)