

7 Core Trailer Cable

pro-POWER

Automotive Wires



Feature:

- 7 core trailer cable : 1 × 28 / 0.3 mm + 6 × 14 / 0.3 mm plain copper, PVC insulated, BS6862, cores with an overall black PVC sheathed

Specifications:

Conductors

Plain annealed copper bunch meeting the requirements of BS 6360 where applicable and BS 6862

6 cores, 1 mm² (14 / 0.3 mm)

1 cores, 2 mm² (28 / 0.3 mm)

Insulation

Type T11 PVC compound meeting the requirements of BS 7655

Minimum average radial thickness = 0.6 mm

Lay Up

Centre, (28 / 0.3 mm), White

Outer, (14 / 0.3 mm), Red, Green, Brown, Blue, Black and Yellow

Sheath

Type 6 PVC compound meeting the requirements of BS 7655

Minimum average radial thickness = 0.8 mm

Service data

Maximum Conductor operating temperature 70°C

Specification Table

Minimum Overall Diameter	Maximum Overall Diameter	Maximum Rated Voltage (V)	Length (m)	Part Number
9.7	10.2	100	100	BZ-1428P-NT40-AXX-64

Dimensions : Millimetres (Unless Specified)

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com

www.farnell.com

www.newark.com

www.cpc.co.uk

pro-POWER

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[0301CV100W](#) [04JSBLACK](#) [06JSBLACK](#) [08450046010](#) [08450056010](#) [08450066010](#)
[08450166010](#) [08450236010](#) [08450256010](#) [08JSBLACK](#) [10026B](#) [10026BK](#) [10026G](#)
[10026R](#) [10026TB](#) [10026TBK](#) [10026TG](#) [10026TR](#) [10026TW](#) [10026W](#) [10030B](#)
[10030BK](#) [10030G](#) [10030O](#) [10030R](#)