Capacitive proximity sensors

CFAM 30P1600

dimension drawing		
SW 36		photo
general data		
nominal sensing distance Sn	15 mm	
nominal sensing distance Sn adjustable	4 15 mm	
mounting type	flush	connection diagram
GND electrode	yes	connection diagram
temperature drift	± 15 % (+10 +70 °C)	
sensitivity adjustment	potentiometer, 18 turn	BN (1)
output indicator	LED yellow	DND BK (4)
		BU (3)
electrical data		
voltage supply range +Vs	10 30 VDC	
current consumption max. (no load)	20 mA	сс 🕠 гог
output circuit	PNP make function (NO)	
output current	< 200 mA	
voltage drop Vd	< 1,5 VDC	
switching frequency	< 50 Hz	
short circuit protection	yes	
reverse polarity protection	yes	
mechanical data		
type	cylindrical threaded	
housing material	brass nickel plated	
dimension	30 mm	
housing length	71 mm	
connection types	cable, 2 m	
ambient conditions		
operating temperature	-25 +75 °C	
protection class	IP 65	
field of application		
detection of non-conductive media	yes	
fill level detection through container	yes	
liquids in direct contact	no	
object detection / bulk goods	yes	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Capacitive Touch Sensors category:

Click to view products by Baumer manufacturer:

Other Similar products are found below :

CP8186AT LC717A10AJ-AH CP7709DT AT42QT1012-MAH FK 8-1 SMBTASK3KIT6 LC717A10AR-NH MCP2036T-I/MG CP3155T QT113BISG CAP1166-1-CZC-TR CM12-08EBP-KW1 CR12CN04DPO-E2 CR30SCF10ATO CR30SCF10DPO BCS M30BBI2-PSC15D-S04K CA30CAF16PAM1 VC12RN230 XT130B1FBL2 FDC1004DGSR FDC1004DGST CR18SCF05DPO CR30CN15DPO-E2 VC12RT23010M CDWM3020ZPM 17-8421-226 VC12RN924 AT42QT1050-MMH AT42QT1050-MMHR AT42QT1110-AU AT42QT1244-AU AT42QT1244-AU AT42QT1481-AUR OTBA5L OTBVR81LQD PBCL22T SM31RDLBQD AT42QT1111-MU AT42QT1244-MU AT42QT2100-MUR AT42QT2120-MMHR VTBN6LQ MTCH6102-IMV CAP1128-1-BP-TR CA30CAF16PA STMPE16M31QTR STMPE16M31PXQTR STM8T143-EVAL XT230A1PAL2 LC717A00AR-NH