

Spindle cable/Single core | TPE | chainflex® CFROBOT

- For torsion applications
- TPE outer jacket
- Shielded
- Oil-resistant, bio-oil-resistant
- PVC-free
- UV-resistant
- Flame retardant
- Hydrolysis and microbe-resistant

Dynamic information

	Bend radius	e-chain® twisted	minimum 10 x d
		flexible	minimum 8 x d
		fixed	minimum 5 x d
	Temperature	e-chain® twisted	-35 °C to +90 °C
		flexible	-45 °C to +100 °C (following DIN EN 60811-504)
		fixed	-50 °C to +100 °C (following DIN EN 50305)
	v max.	twisted	180 °/s
		a max.	60 °/s²
	Travel distance	Robots and multi-axis movements, Class 1	
	Torsion	± 180°, with 1 m cable length, Class 3	

Cable structure

	Conductor	Extremely bend-resistant cable.
	Core insulation	Mechanically high-quality TPE mixture.
	Overall shield	Extremely torsion-resistant tinned braided copper shield. Coverage approx. 90 % optical
	Outer jacket	Low-adhesion, extremely abrasion-resistant and highly flexible TPE mixture, adapted to suit the requirements in e-chains®. Colour: Jet black (similar to RAL 9005)

Electrical information

	Nominal voltage	600/1000 V (following DIN VDE 0298-3)
	Testing voltage	4000 V (following DIN EN 50395)

Properties and approvals

	UV resistance	High.
	Oil resistance	Oil resistant (following DIN EN 60811-404), bio-oil resistant (following VDMA 24568 with Plantocut 8 S-MB tested by DEA), Class 4.
	Flame retardant	According to IEC 60332-1-2, CEI 20-35, FT1, VW-1
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992).

Example image

Basic requirements	low	1	2	3	4	5	6	7	highest
Travel distance	unsupported	1	2	3	4	5	6	7	≥ 400 m
Oil resistance	none	1	2	3	4	5	6	7	highest
Torsion	none	1	2	3	4	5	6	7	± 180°

Class 6.1.4.3

	UL/CSA	Style 10258 and 21387, 1000 V, 90 °C
	NFPA	Following NFPA 79-2012 chapter 12.9.
	EAC	Certificate no. RU C-DE.ME77.B.02324 (TR ZU)
	CTP	Certificate no. C-DE.PB49.B.00420 (Fire safety)
	CEI	Following CEI 20-35.
	Lead-free	Following 2011/65/EU (RoHS-II).
	Cleanroom	According to ISO Class 1. Outer jacket material complies with CF34.UL.25.04.D, tested by IFA according to standard 14644-1.
	CE	Following 2014/35/EU.

Guaranteed lifetime according to guarantee conditions (Page 22-23)

Cycles*	5 million		7.5 million		10 million	
	Temperature, from/to [°C]	Torsion max. [°/m]	Temperature, from/to [°C]	Torsion max. [°/m]	Temperature, from/to [°C]	Torsion max. [°/m]
-35/-25	±150	-25/+70	±180	-35/-25	±90	±30
-25/+70	±180	+70/+80	±150	-25/+70	±120	±60
+70/+80	±150			+70/+80	±90	±30

* Higher number of cycles? Online lifetime calculation: www.igus.eu/chainflexlife

Typical mechanical application areas

- For extremely heavy duty applications with torsional movements
- Almost unlimited resistance to oil, also with bio-oils
- Indoor and outdoor applications, UV resistant
- Especially for robots and multi-axis movements
- Robots, Handling, spindle drives

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CFROBOT.035	(1x10.0)C	10.5	134	209
CFROBOT.036	(1x16.0)C	12.0	202	293
CFROBOT.037	(1x25.0)C	14.5	318	454
CFROBOT.038	(1x35.0)C	15.5	431	574
CFROBOT.039 ¹¹⁾	(1x50.0)C	18.0	601	781

¹¹⁾ Phase-out model
Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Paired Cables](#) category:

Click to view products by [Igus](#) manufacturer:

Other Similar products are found below :

[7-21000-9](#) [9805 060100](#) [1416402/M12MS/IP20/10](#) [9804 060100](#) [9808 060100](#) [9843 060100](#) [9873 060100](#) [190-038045-00](#) [44A0121-12-996CS2275](#)
[44A0121-20-09-MX](#) [55PC0211-14-9](#) [55PC0216-24-9](#) [55PC0221-22-2/6CS2756](#) [55PC0811-16-9](#) [55PC0811-24-9](#) [55PC1131-20-029-9](#) [Y60912](#)
[CW1922-000](#) [RI55D](#) [9157 060100](#) [2020D0309-0](#) [9774 060100](#) [8334 060100](#) [1350SB 0101000](#) [8342 060100](#) [8740 060U1000](#) [9505 060U1000](#)
[3613 003A1000](#) [44A0121-22-0/9-MX](#) [2412 009U1000](#) [82777 8771000](#) [9406 T35100](#) [3613 D151000](#) [1533R 0101000](#) [1533P 0101000](#) [9272](#)
[006U1000](#) [2413F D15A500](#) [9681 0601000](#) [44A0121-22-6/9-MX](#) [1533R 0061000](#) [RIT1000](#) [1533R 006A1000](#) [9812 060100](#) [2221 B59U1000](#)
[10GX13 D151000](#) [1874A 004A1000](#) [8340 060100](#) [8333 0601000](#) [1533R 0021000](#) [1583A 012U1000](#)