

# Microstrobe

Patent applied for.

## Xenon Flashing Panel Mount Indicator



- High intensity Xenon flash
- Multivoltage (10–100Vdc 20–72Vac) 110Vac and 230Vac
- Simple to install
- Compact one-piece housing
- Standard 22mm hole pattern
- Fully weatherproof to IP67 (front)
- Five lens colours



The Microstrobe is a compact and reliable high intensity Xenon indicator for use in panel mount applications. Quick and simple to install with instant visibility and status recognition.

 **delta design**  
a division of NICOTECH Limited

**.. simply brilliant**

# Microstrobe

## Xenon Flashing Panel Mount Indicator

### technical specification

MODEL	VOLTAGE RANGE	POWER OUTPUT	CURRENT CONSUMPTION (mA)				FLASH RATE NOMINAL	WEIGHT (Gms)
			@12V	@24V	@60V	@100V		
XP4XMV/1	10–100Vdc 20–72Vac	1W	190	105	55	29	75/min	50
XP4X110/1	99–121Vac	1W	-	-	-	-	75/min	50
XP4X230/1	207–253Vac	1W	-	-	-	-	75/min	50

Strobe unit weatherproof to IP67 when installed (front only). Operating temperatures: -20°C to +50°C.  
High Voltage transient and polarity reversal protection fitted.  
CE – complies with EMC directive 89/336/EEC and Low Voltage Directive 73/23/EEC, where appropriate.



### dimensions

Lamp Unit: 23mm x 36mm dia.  
Drive unit case assembly: 35mm x 35mm x 43mm  
Depth behind panel: 45mm

### materials and lens colours

Polycarbonate lamp unit. ABS back box.



### 12 months guarantee



 **delta design**  
a division of NICOTECH Limited



Primrose Hill, Kings Langley,  
Herts WD4 8ST, England.

Tel: (U.K.) 01923 269522  
(Int.) +44 1923 269522

Fax: (U.K.) 01923 260167  
(Int.) +44 1923 260167

E-mail: [sales@deltadesign.co.uk](mailto:sales@deltadesign.co.uk)  
Web: <http://www.deltadesign.co.uk>

**Your Delta Design distributor:**

All specifications are nominal and subject to change without notice.

# Microstrobe

Patent applied for.

## Xenon Flashing Panel Mount Indicator



- High intensity Xenon flash
- Multivoltage (10–100Vdc 20–72Vac) 110Vac and 230Vac
- Simple to install
- Compact one-piece housing
- Standard 22mm hole pattern
- Fully weatherproof to IP67 (front)
- Five lens colours



The Microstrobe is a compact and reliable high intensity Xenon indicator for use in panel mount applications. Quick and simple to install with instant visibility and status recognition.

 **delta design**  
a division of NICOTECH Limited

**.. simply brilliant**

# Microstrobe

## Xenon Flashing Panel Mount Indicator

### technical specification

MODEL	VOLTAGE RANGE	POWER OUTPUT	CURRENT CONSUMPTION (mA)				FLASH RATE NOMINAL	WEIGHT (Gms)
			@12V	@24V	@60V	@100V		
XP4XMV/1	10–100Vdc 20–72Vac	1W	190	105	55	29	75/min	50
XP4X110/1	99–121Vac	1W	-	-	-	-	75/min	50
XP4X230/1	207–253Vac	1W	-	-	-	-	75/min	50

Strobe unit weatherproof to IP67 when installed (front only). Operating temperatures: -20°C to +50°C. High Voltage transient and polarity reversal protection fitted. CE – complies with EMC directive 89/336/EEC and Low Voltage Directive 73/23/EEC, where appropriate.



### dimensions

Lamp Unit: 23mm x 36mm dia.  
Drive unit case assembly: 35mm x 35mm x 43mm  
Depth behind panel: 45mm

### materials and lens colours

Polycarbonate lamp unit. ABS back box.



### 12 months guarantee



 **delta design**  
a division of NICOTECH Limited



Primrose Hill, Kings Langley,  
Herts WD4 8ST, England.

Tel: (U.K.) 01923 269522  
(Int.) +44 1923 269522

Fax: (U.K.) 01923 260167  
(Int.) +44 1923 260167

E-mail: [sales@deltadesign.co.uk](mailto:sales@deltadesign.co.uk)  
Web: <http://www.deltadesign.co.uk>

**Your Delta Design distributor:**

All specifications are nominal and subject to change without notice.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Delta manufacturer](#):*

Other Similar products are found below :

[MKEL-DRB](#) [1316038K66E000](#) [DOP-EXI014RAE](#) [DRP048V240W1BN](#) [DTB4824LV](#) [DTB4848LV](#) [DTB4896CR](#) [DTB4896VRE](#)  
[DTB9696CVE](#) [DTB9696LVE](#) [DVP01PU-S](#) [DVP06XA-S](#) [DVP08SN11T](#) [DVP08SP11R](#) [DVDPNET-SL](#) [DVPDT01-S](#) [EFB0405VHD](#)  
[EFB0412HHA](#) [BUE-20015](#) [IFD8520](#) [20114-80](#) [20240-82](#) [20310-80](#) [21022-82](#) [S24SP15003PDFA](#) [LNE-12V185WAAA](#) [LNE-](#)  
[24V100WDAA](#) [LNE-36V185WAAA](#) [LNE-54V185WDAA](#) [ADP485-01](#) [FFB1212VHE-F00](#) [20243-81](#) [23595-73](#) [PMH-24V150WCBA](#)  
[CME-COP01](#) [31000-82](#) [32003-81](#) [32007-82](#) [32007-84](#) [TP05G-BT2](#) [TP-PCC](#) [53682-83](#) [53761-81](#) [31003-82](#) [31004-84](#) [31007-84](#)  
[BR200W250](#) [32003-82](#) [VFD015EL23A](#) [DOP-EXI028RAE](#)