



Features

Visible and IR spectral response

ONEX[®] ł


- High reliability
- Oxide passivation
- Linear short circuit current
- Low capacitance, high speed
- Protective coating

Description


The Silonex series of silicon solderable planar photodiodes feature low cost, high reliability, and linear short circuit current over a wide range of illumination. These devices are widely used for light sensing and power generation because of their stability and high efficiency. They are particularly suited to power conversion applications due to their low internal impedance, relatively high shunt impedance, and stability. The photodiodes have a protective coating that protects them from humidity effects. These devices also provide a reliable and inexpensive detector for instrumentation and light beam sensing applications.

Absolute Maximum Ratings

Storage Temperature	-40°C to +105°C
Operating Temperature	-40°C to +105°C



Also available without leads as part number SLCD 61N2



Symbol	Parameter	MIN	TYP	MAX	UNITS	TEST CONDITIONS
I _{SC}	Short Circuit Current	0.7	1.2			V _R =0V, Ee=25mW/cm ² (1)
V _{oc}	Open Circuit Voltage		0.40		V	Ee=25mw/cm ² (1)
I _D	Reverse Dark Current			3.3	μA	V _R =5V, Ee=0
CJ	Junction Capacitance		0.7		nF	V _R =0V, Ee=0, f=1MHz
S _λ	Spectral Sensitivity		0.55		A/W	λ=940nm
V _{BR}	Reverse Breakdown Voltage	20			V	I _R =100μA
λ_{P}	Maximum Sensitivity Wavelength		930		nm	
λ_R	Sensitivity Spectral Range	400		1100	nm	
θ _{1/2}	Acceptance Half Angle		60		deg	(off center-line)

Electrical Characteristics (T_A=25°C unless otherwise noted)

Notes: (1) Ee = light source @ 2854 °K

Specifications subject to change without notice 101429 REV 5

5200 St. Patrick St., Montreal Que., H4E 4N9, Canada Tel: 514-768-8000 Fax: 514-768-8889

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Advanced Photonix manufacturer:

Other Similar products are found below :

NSL-32SR3 SLCD-61N5 NSL 4962 SLD-70 BG2A NSL 06S53 NORPS-12 NSL 19M51