

Multimeter



USB



Specifications

Basic Functions	Range	Best Accuracy
DC Voltage	200 mV / 2 V / 20 V / 200 V / 1,000 V	± (0.05% + 5)
AC Voltage	2 V / 20 V / 200 V / 1,000 V	± (0.6% + 40)
AC Bandwidth	100 KHz	
DC Current	200 µA / 2,000 µA / 20 mA / 200 mA / 10 A	± (0.15% + 20)
AC Current	200 µA / 2,000 µA / 20 mA / 200 mA / 10 A	± (0.8% + 15)
Resistance	200 Ω / 2 kΩ / 20 kΩ / 200 kΩ / 2 MΩ / 20 MΩ	± (0.4% + 20)
Capacitance	20 nF / 200 nF / 2 µF / 20 µF / 200 µF / 2 mF / 20mF	± (1.2% + 20)
Temperature (°C)	-40°C to 1,000°C	± (1% + 3)
Temperature (°F)	-40°F to 1,000°F	± (1.5% + 50)
Frequency	20 Hz / 200 Hz / 2 KHz / 20 KHz / 200 KHz / 2 MHz / 20 MHz / 200 MHz	± (0.1 % + 15)
Duty cycle	10% to 90%	± (1% + 30)
Special Functions		
Fused 10 A range	✓	
Auto ranging	✓	
Current measurement alarm	✓	
Function set up	✓	
Voltage & current : AC + DC measurement	✓	
Data logging	100	
Data recall	✓	
Diode	✓	
Continuity buzzer	✓	
True RMS	✓	
Peak hold	✓	
Maximum / minimum mode	✓	



Multimeter

USB



Special Functions

Relative mode	✓
Data hold	✓
USB	✓
Double display backlight	✓
Full icon display	✓
Sleep mode	✓
Low battery display	✓
Input impedance for DC voltage measurement	DC 200mV : around 2.5 GΩ All other ranges : 10 MΩ
Maximum display	20,000
Analogue bar graph	✓

General Characteristics

Power	9 V battery (6F22)
LCD size	73 x 50 mm
Product colour	Orange and grey
Product net weight	384 g
Product size	200 x 93 x 40 mm
Standard accessories	Test lead, battery, English manual, point contact temperature probe, alligator clip, test clip, USB interface cable, software, carrying bag
Standard individual packing	Gift box

Part Number Table

Description	Part Number
Multimeter, USB	72-7730

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA™ is the registered trademark of the Group. © Premier Farnell plc 2011.



X-ON Electronics

Authorized Distributor

Click to view similar products for [Tenma manufacturer](#).

Other Similar products are found below :

[2110130UKEU](#) [2110140](#) [2110142](#) [2110144](#) [2110146](#) [2110148](#) [2110150](#) [2110152](#)
[2110154](#) [2110156](#) [2110158](#) [2110160](#) [2110162](#) [2110164](#) [2110168](#) [2110170](#) [211040](#)
[211041](#) [211042](#) [211045](#) [211046](#) [211047](#) [211050](#) [2110562](#) [2110563](#)