

The 2803 USB serial I/O adapter provides eight RS-232, RS-422, or RS-485 serial ports for USB connectivity to legacy or non-USB compliant devices. Each port is individually configurable for RS-232, RS-422, or RS-485. Simply install the included software and connect the 2803 serial interface adapter to your USB port. The device is immediately recognized by the system. Now your non-USB peripherals can have the same connection simplicity and ease of use as USB aware peripherals.

Sealevel Systems provides I/O solutions for connectivity technology. Sealevel's commitment to providing the best I/O solutions is reflected in the [Lifetime Warranty](#) that is standard on all Sealevel manufactured I/O products.



- ▶▶ Each port individually configurable for as RS-232, RS-422, or RS-485
- ▶▶ High speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO
- ▶▶ Data rates to 921.6K bps
- ▶▶ Automatic RS-485 enable/disable
- ▶▶ Serial and USB activity LEDs
- ▶▶ Hot-swappable
- ▶▶ Powered by USB connection
- ▶▶ DB-9M connectors
- ▶▶ 72" USB cable included

TECHNICAL SPECIFICATIONS	
Number of Ports	8
Communications Chip	USB/UART
Max. Data Rate	921.6K bps
Max. Data Distance	4000 feet
USB Spec.	1.1 Compliant 2.0 Compatible
Operating Temperature	0 - +70°C
Storage Temperature	-50° - +105°C
Humidity Range	10 - 90% R.H.
Dimensions	8.7" (L) x 6.1" (W) x 2.0" (H)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [SEALEVEL](#) manufacturer:

Other Similar products are found below :

[SEALEVEL](#)