

Single-core general purpose cable for use in conduit and trunking.

Description

Applications

Protected installations inside appliances and in conduit, lighting or trunking.

Design

Conductor : Stranded copper complying with BS6360, class 2.

Insulation : PVC-compound complying to BS7655: section 3.1, type T11

Marking

- All cables(Black Print):)(H07V-R <HAR> BS6004 size CU/PVC)(H07V-R <HAR> BS6004 BASEC
- All cables(Embossed):)(ELECTRIC CABLE 450/750V BS6004 BASEC <HAR>)(

Core Identification


- Single core available in Green/Yellow, Blue, Brown Black or Grey.



Standards

International HD 21.3

National BS 6004



Operating temperature, range
5 .. 70 °C

BS6004 - 6491X

Contact

Cables for General Construction Market


Nexans Logistics Ltd, Nexans House, Chesney Wold, Bleak Hall

MK6 1LA Milton Keynes

United Kingdom

Phone: 01908 250850

terry.morton@nexans.com



Operating temperature, range
5 .. 70 °C

Characteristics
Construction characteristics

Conductor material	Copper
Conductor flexibility	Stranded class 2
Insulation	PVC

Dimensional characteristics

Number of cores	1
-----------------	---




Electrical characteristics

Rated Voltage U ₀ /U	450 / 750 V
---------------------------------	-------------

Usage characteristics

Operating temperature, range	5 .. 70 °C
Maximum core temperature still	70 °C

Product List

Nexans ref.	Name	Conductor cross-section (mm ²)
	BS6004 1x 10 mm ²	10
	BS6004 1x 16 mm ²	16
	BS6004 1x 25 mm ²	25
	BS6004 1x 35 mm ²	35
	BS6004 1x 50 mm ²	50
	BS6004 1x 70 mm ²	70
	BS6004 1x 95 mm ²	95
	BS6004 1x120 mm ²	120
	BS6004 1x150 mm ²	150
	BS6004 1x185 mm ²	185
	BS6004 1x240 mm ²	240
	BS6004 1x300 mm ²	300
	BS6004 1x400 mm ²	400
	BS6004 1x500 mm ²	500
	BS6004 1x630 mm ²	630

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Nexans manufacturer:

Other Similar products are found below :

[M22759/34-16-0](#) [3X1YY50](#) [M22759/41-20-9](#) [M81044/12-16-2](#) [M16878/4-BGE-9](#) [M27500-20ML1T08](#) [2112/10-1SJ-22](#) [30-286-22-1](#)
[EN2714-013B004F](#) [M22759/87-16-96](#) [M81044/9-8-9](#) [SUPERPOL 10](#) [2112/10-14\(GAW805AB14\)](#) [M22759/87-12-9](#) [M22759/34-22-2](#)
[M22759/92-20-2](#) [EN2714-013A004F](#) [M22759/44-16-9](#) [M22759/34-16-9](#) [13-DRX24X02P](#) [M22759/187-16-96](#) [13-DRX22X02R](#) [M22759/43-](#)
[24-6](#) [M22759/41-24-9](#) [M27500-24SB1T23](#) [M22759/81-22-5](#) [M81044/12-16-5](#) [30-284-14-2](#) [M27500-24SN3N23](#) [M22759/43-24-8](#)
[M81044/9-10-9](#) [M27500-20SD1T23](#) [M22759/33-26-7](#) [M22759/43-10-9](#) [HM2N18-9](#) [2698096-5999](#) [M22759/91-12-9](#) [M22759/43-24-5](#)
[M22759/43-24-7](#) [13-DRX23P03P](#) [13-DRS26P04P-V1](#) [30-285-22-2](#) [M27500-22TG5T14](#) [M22759/33-26-3](#) [M22759/11-20-9](#) [M22759/91-20-2](#)
[M22759/87-16-6](#) [HM2N24-9](#) [M27500-16SM2N23](#) [30-284-18-3](#)