


TPSR THERMISTOR SENSOR

TPSR-SENSOR

X10308



SPECIFICATIONS

Heatshrink rated up to:

Epoxy mix rated up to:

Cable: 7/0.2 core. P.T.F.E./E.T.F.E. insulated rated at:

125°C

120°C

120°C

125°C

120°C

155°C

155°C

105°C

Insulation resistance: 10M ohm at 100VDC min

Thermistor: 220K ohm at 25°C /Beta value 4461

RECOMMENDATIONS

Other documents, which may be appropriate for your application, are available on request.

CODEIDENTITYDESCRIPTIONX10284TPSRTPSR data sheet

X10229 RFI Single Phase Filter recommendations: Addressing the EMC Directive.

X10213 ITA Interaction: Uses for phase angle and for burst fire control.

X10255 SRA Safety requirements: Addressing the Low Voltage Directive (LVD)

including, Thermal data/cooling, Live parts warning, Earth

requirements and fuse recommendations.

AP02/4 COS UAL Conditions of sale.

<u>NOTE:</u> It is recommended that installation and maintenance of this equipment should be carried out by suitably qualified/trained personnel with reference to the current edition of the I.E.E. wiring regulations BS7671. The regulations contain important requirements regarding the safety of electrical equipment. For International Standards refer to I.E.C/ Directive IEC 950.

ORDER CODE State part number:

A84018: TPSR Thermistor Assembly.
A01825: TPSR-25/25A 230v AC controller



UNITED AUTOMATION LIMITED

1Southport Business Park Kew Southport, PR8 4HQ ENGLAND Tel: 0044 (0) 1704 - 516500 Main Tel: 0044 (0) 1704 - 516516 Sales Fax: 0044 (0) 1704 - 516501 Enquiry@united-automation.com



This document was created with Win2PDF available at http://www.daneprairie.com. The unregistered version of Win2PDF is for evaluation or non-commercial use only.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for United Automation manufacturer:

Other Similar products are found below:

FC36M BM3 QVR/S-RFI 17 ZVS16DV F175-25A CSR604A CSR1004A AFM-11 F155-10A PAC2 DCM-24-40 CSR2-10E CSR2-15E CSR1504A PSR-25