## **Detailed Specifications & Technical Data**

**METRIC MEASUREMENT VERSION** 



## 83048 Hook-up/Lead - UL AWM Style 1371

For more Information please call

1-800-Belden1



## **Description:**

Stranded silver-coated copper conductor insulation with extruded TFE Teflon.

## **Physical Characteristics (Overall)**

### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	24	19x36	SPC - Silver Plated Copper

### Insulation

### Insulation Material:

Insulation Material	Wall Thickness (mm)
TFE - Tetrafluoroethylene	0.1524

### **Overall Insulation Overall Cabling**

**Overall Nominal Diameter:** 0.914 mm

## **Applicable Specifications and Agency Compliance (Overall)**

## **Applicable Standards & Environmental Programs**

UL AWM Style:	1371
UL Rating:	105°C
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	MIL-W-16878/6
MIL Spec Rating:	250 V, 200°C
ame Test	
UL Flame Test:	VW-1
enum/Non-Plenum	

# Fla

### Ple

Plenum (Y/N): No

## **Related Documents:**

No related documents are available for this product

### **Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83048 001100	30 MT	0.045 KG	BROWN	E	#24 STR TFE BRN

## **Detailed Specifications & Technical Data**

### METRIC MEASUREMENT VERSION



### 83048 Hook-up/Lead - UL AWM Style 1371

83048 0011000	305 MT	0.907 KG	BROWN	ES	#24 STR TFE BRN
83048 002100	30 MT	0.045 KG	RED	E	#24 STR TFE RED
83048 0021000	305 MT	0.907 KG	RED	ES	#24 STR TFE RED
83048 003100	30 MT	0.045 KG	ORANGE	E	#24 STR TFE ORG
83048 0031000	305 MT	0.907 KG	ORANGE	ES	#24 STR TFE ORG
83048 005100	30 MT	0.045 KG	GREEN, DARK	E	#24 STR TFE GRNDK
83048 0051000	305 MT	0.907 KG	GREEN, DARK	ES	#24 STR TFE GRNDK
83048 0071000	305 MT	0.907 KG	VIOLET	ES	#24 STR TFE VIO
83048 008100	30 MT	0.045 KG	GRAY	E	#24 STR TFE GRY
83048 0081000	305 MT	0.907 KG	GRAY	ES	#24 STR TFE GRY
83048 010100	30 MT	0.045 KG	BLACK	E	#24 STR TFE BLK
83048 0101000	305 MT	0.907 KG	BLACK	ES	#24 STR TFE BLK

### Notes:

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25' S = STRIPING ADDERS FOR TYPES E AND EE: 123 STRIPES. MINIMUM ORDER10

Revision Number: 1 Revision Date: 05-14-2007

© 2011 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Page 2 of 2 05-10-201

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Belden manufacturer:

Other Similar products are found below:

HIPWP2LA AX270172 8916-BRN-100 8916-GRN/YEL-500 8916-YEL-500 8917 002100 8917-005-500 8917-GRN/YEL-100 8918-GRY-1000 8919-BRN-1000 8919-DK-BLU-100 8920-BRN-1000 8920-GRY-1000 8920-RED-1000 7805R-GRY-100 7810A-BLK-500 8104-CHR-500 8108-CHR-100 8125-CHR-100 8132-CHR-1000 8133-CHR-1000 8155-CHR-1000 8162-CHR-1000 8164-CHR-100 8164-CHR-1000 8185-CHR-1000 8205-CHR-1000 8218-BLK-1000 8221-BLK-1000 8233-BLK-1000 8237-BLK-500 8238-BLK-500 8240-BLK-U1000 8241A-BLK-1000 8262-BLK-1000 8268-BLK-500 8279-BLK-1000 83002 0041000 83002 0101000 83003-VIO-100 83003-VIO-500 83004 0051000 83006 0041000 83007 0081000 83008-WHT-1000 83010-BRN-100 83010-DK-GRN-1000 83023-BRN-100 83023-DK-GRN-100