

Differential pressure measuring instrument

testo 510 – Pocket-sized differential pressure measurement

Differential pressure measurement 0 to 100 hPa

Flow velocity measurement possible with Pitot tube

Temperature and air density compensation

Display illumination

10 selectable units



hPa

Illustration 1.1

testo 510 measures differential pressure in the range from 0 to 100 hPa. The differential pressure measurement is temperature-compensated for accurate measurement values. The measurement values can be displayed in Pascal over the entire measurement range. Magnets at the rear permit free-hand work. The backlit display allows the

measurement values to be easily read out, even in unfavourable light conditions. The testo 510, in combination with a Pitot tube, measures air flow velocity. For accurate measurement values, the air density can be compensated. testo 510 is very handy, small and easy to operate.

Technical data / Accessories

testo 510

testo 510 handy measuring instrument for differential pressure incl. protection cap, batteries and calibration protocol

Part no. 0560 0510



Sensor type **Differential pressure sensor**

Meas. range	0 to 100 hPa
Accuracy ±1 digit	±0.03 hPa (0 to 0.30 hPa) ±0.05 hPa (0.31 to 1.00 hPa) ±(0.1 hPa + 1.5 % of mv) (1.01 to 100 hPa)
Resolution	0.01 hPa

General technical data

Positive pressure	500 mbar
max. static pressure	1.5 bar
Oper. temp.	0 to +50 °C
Storage temp.	-40 to +70 °C
Selectable units	hPa, mbar, Pa, mmH2O, inH2O, inHg, mmHg, psi, m/s, fpm
Protection class	IP40
Battery type	2 batteries Type AAA
Battery life	50 h (average, without display illumination)
Measurement rate	0.5 s
Dimensions	119 x 46 x 25 mm
Weight	90 g (with batteries and protective cap)
Warranty	2 years

0981 9764/msp/A/01.2012

Accessories

Part no.

Accessories for measuring instrument

Connection hose, silicone, 2 m long, max. load 700 hPa (mbar)	0554 0448	
ISO calibration certificate pressure; differential pressure; 3 points distributed over meas. range	0520 0095	
ISO calibration certificate pressure; differential pressure; 5 points distributed over meas. range	0520 0005	

Subject to change without notice.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Testo manufacturer:](#)

Other Similar products are found below :

[206 PH1](#) [TESTO 316-1 0632 0316](#) [TESTO 470 0563 0470](#) [TESTO 770-1 0590 7701](#) [TESTO 905-T1 0560 9055](#) [0572 0500](#) [0590 0016](#) [0602 4592](#) [0590 0008](#) [0590 0018](#) [0602 0645](#) [0635 1025](#) [0628 0020](#) [TESTO 435-2 0563 4352](#) [TESTO 605I 0560 1605](#) [TESTO 755-2 0590 7552](#) [TESTO 770-2 0590 7702](#) [TESTO 869 + TESTO 745](#) [TESTO 869 + TESTO 750-3 465 410-2 460 0572 6172 0590 0001 0614 2272](#) [TESTO 417 0560 4170](#) [0609 7072](#) [TESTO 174-H SET](#) [TESTO 176-T4](#) [TESTO 176-P1](#) [TESTO 830-T2](#) [TESTO 103](#) [TESTO 905-T1](#) [TESTO 108-2](#) [TESTO 905I](#) [TESTO 108 0563 4403](#) [0590 7703](#) [TESTO 435-3 0560 4353](#) [TESTO 735-1 0560 7351](#) [TESTO 760-3 0590 7603](#) [TESTO 770-3 0590 7703](#) [0590 0013](#) [0602 4892](#) [TESTO 635-2 0563 6352](#) [TESTO 750-3 0590 7503](#) [TESTO 760-1 0590 7601](#) [816-1](#) [TESTO 174-T SET](#) [TESTO 605-H1](#)