

Specification :

Material :

- 1. Plastic Housing : ABS, UL94V-0.
- 2. RJ45 Housing : PBT, UL94V-0.
- 3. RJ45 Contact material & finished :
 - 3-1. Phosphor Bronze with 30-40 micro-inch Nickel plated.
 - 3-2. Contact area : Min. 3mm 50 micro-inch Gold plated.



Performance :

- a. The sticker color codes combine two wirings of T568A & T568B.
- b. Insertion Force : 900 gms for 8 contacts.
- c. Retention Strength : 7.7 kgs between Jack and Plug.
- d. Operation Temperature : -40°C to 80°C.
- e. Durability :
 - e-1. Jack : 750 cycles Plug-Jack mating and unmating test, Insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.

Remark : JE315- /XX
(1)

- (1) XX Plastic Color
 - WH=White BK=Black
 - GN=Green RD=Red
 - OR=Orange

RoHS Compliant

 	DSGN	CSQ	21.MAY.2007	ITEM NO: 4261
	CHK	Maer	21.MAY.2007	
UNIT	M/M	APPR	Yty	Unshield In-line Coupler
SCALE	1/1			
DWG NO: 4261	Videk Ltd			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Videk manufacturer](#):

Other Similar products are found below :

[1962-10B](#) [1054](#) [2409M-3](#) [2129HQ-5](#) [1996-15](#) [1961-25G](#) [2259](#) [2996AS-5Y](#) [2965-20Y](#) [2965-30W](#) [1514](#) [2129HQ-1](#) [1963-3](#) [1962-10R](#)
[1961-10](#) [1996-10B](#) [1996-1B](#) [2965-30G](#) [2965-8G](#) [2965-30B](#) [2993-3RG](#) [2996-1G](#) [2996-5B](#) [2996AS-5G](#) [2996AS-3](#) [2965-15BK](#) [1996-2](#)
[2417-3](#) [1965-10X](#) [1961-1B](#) [9301-5](#) [2961-30R](#) [2965-8B](#) [2996AS-1G](#) [3089-2](#) [1961-25B](#) [1961-50](#) [2961-0.5G](#) [2961-30BK](#) [2961-3BK](#) [2965-](#)
[5PR](#) [8920-7.6](#) [2961-30Y](#) [2965-10B](#) [2965-10Y](#) [2992-5](#) [2996-0.5Y](#) [2996-5R](#) [2129GHQ-5](#) [2965-15B](#)