



Specification :

Material :

1. RJ45 Jack :
 - 1-1. Housing : ABS, UL 94V-0, with Black color.
 - 1-2. Contact Bracket : PC, UL 94V-2, Transparent color.
2. RJ45 Jack Contact :
 - 2-1. Material : Phosphor Bronze with Nickel plated.
 - 2-2. Finish : 50 micro-inch Gold plated on Plug contact area.
3. RJ45 Jack Shield : Bronze with Nickel Plated.
4. PCB : FR4, UL 94V-0.

Performance :

- a. Insertion force : 30N max. (IEC 60603-7-5).
- b. Retention strength : 7.7 kg between Jack and Plug.
- c. Operating temperature : -10°C to 60°C. (ISO/IEC 11801, ANSI/TIA/EIA 568 B.2)
- d. Life(mating cycles) : 750 cycles min. (ISO/IEC 11801, IEC 60603-7-5)
- e. The Cat.5e transmission performance is in compliance with the ANSI/TIA/EIA 568 B.2 standard.

GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.005 X.XX ±0.05 X.X ±0.1	DRAWING	17.JUN.2010	QIQI	
	CHECK	17.JUN.2010	JANE	
	APPROVAL	17.JUN.2010	JAIMY	
		DATE	NAME	
SCALE	1/1 (A4)	UNIT	mm	DES.: CAT.5E FULL IN-LINE COUPLER
	DRAWING NO.	AAEBB0101131215 JE315AS-CE(SA5)		
	DRAWING CLASSIFICATION	S	SHEET	1 OF 1



10cm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Videk manufacturer](#):

Other Similar products are found below :

[1962-10B](#) [1054](#) [2409M-3](#) [2129HQ-5](#) [1996-15](#) [1961-25G](#) [2259](#) [2996AS-5Y](#) [2965-20Y](#) [2965-30W](#) [1514](#) [2129HQ-1](#) [1963-3](#) [1962-10R](#)
[1961-10](#) [1996-10B](#) [1996-1B](#) [2965-30G](#) [2965-8G](#) [2965-30B](#) [2993-3RG](#) [2996-1G](#) [2996-5B](#) [2996AS-5G](#) [2996AS-3](#) [2965-15BK](#) [1996-2](#)
[2417-3](#) [1965-10X](#) [1961-1B](#) [9301-5](#) [2961-30R](#) [2965-8B](#) [2996AS-1G](#) [3089-2](#) [1961-25B](#) [1961-50](#) [2961-0.5G](#) [2961-30BK](#) [2961-3BK](#) [2965-](#)
[5PR](#) [8920-7.6](#) [2961-30Y](#) [2965-10B](#) [2965-10Y](#) [2992-5](#) [2996-0.5Y](#) [2996-5R](#) [2129GHQ-5](#) [2965-15B](#)