
RoHS Compliant Pb - Lead Free


Ltr	Revisions	Date	Appr

Electrical Specifications:

Nominal Frequency	25.000	MHz	
Temperature Stability	±50	РРМ Мах	
Aging per Year	±3		
Operating Temperature Range (E	-40 to +85	°C	
Storage Temperature Range	-55 to +125		
Supply Voltage	3.3 ± 5%	Vdc	
Supply Current	12	mA Max	
Output Voltage	Logic High (Voh)	90%	Vdc Min
Output Voltage	Logic Low (Vol)	10%	Vdc Max
Output Symmetry	40 to 60	%	
Output Load	15	pF HCMOS	
Rise and Fall Time	10	ns Max	
Enable-Disable Function	Tri-State	-	

Mechanical Specifications:





Specification Title:

Clock Oscillator
7 x 5 mm SMD
Product Specification
Farnell Order Code: 1538884

Part Number: \$73305-25.000-15-X

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Aker manufacturer:

Other Similar products are found below:

C7S-10.000-12-3030-X C-32.000-18-3050-X CXA-016000-3F7E40 CXAN-032000-3F12F20 C7S-14.7456-12-3030-X CXA-026000-3F7F20 CA4-8.000-18-3050-X CXA-012000-3F4D40 C-6.000-18-3050-X C3E-20.000-12-1010-X D31N-032768-3D1C430 SMB-050000-7BL4A6 49SN-027120-FX20X10 CXAN-016000-3F09D41 49S-011059-FX4X15 C-3.579545-18-3050-X CXA-016384-3D4X20 SMB-125000-7CL4T6 CA-7.3728-18-3050-X C-8.000-18-3050-X SMA-027000-3BL4TD CXAN-040000-3F15D41 SMBN-033333-7BL4T00 CXA-026000-3FCF20 SMA-040000-5CL4T5 CA-11.0592-18-3050-X CXA-039000-7F1X40 C-4.194304-18-3050-X C3E-14.31818-12-3030-X S33305-50.000-X C7S-8.000-12-50100-X1 CA-14.7456-18-3050-X CAA-16.000-18-3050-X C-24.576-18-3050-X D31-032768-BDTD41 C3E-18.432-12-3030-X C7S-12.000-12-3030-X C7S-6.000-12-50100-X1 S53305-50.000-X C5S-12.000-12-3030-X C3E-14.3050-X C3E-16.000-12-50100-X1 CA-8.000-18-3050-X C5S-10.000-12-3030-X C3E-16.000-12-50100-X1 S73305-14.7456-X-15