Ty-Rap®

Mounting Bases, Cable Ties and Accessories

Great for securing cables!

One-Piece Mounting Clamp



- Provides a fast and convenient method of securing bundles
- Single-piece design offers reduced installation time and maximized inventory control
- Integral top cover incorporates a unique ratchet design that is fully adjustable and releasable
- Available in a pressure-sensitive adhesive or screw mount design

CLAMPING AREA

				GLAIVIF			
STD. PKG. CAT. NO.	BULK PKG. Cat. No.	BASE STYLE	MAXIMUM HEIGHT (IN.)	MINIMUM IN./MM	MAXIMUM IN./MM	STD. PKG. QTY.	BULK PKG. QTY.
TC5349A-TB	TC349A-TB	SRA* Adhesive	.57	.18 x .24/4.57 x 6.10	.035 x .24/.89 x 6.10	100	1,000
TC5350A-TB	TC350A-TB	SRA* Adhesive	.89	.20 x .59/5.08 x 14.99	.45 x .59/11.43 x 14.99	100	1,000
TC5350-TB	_	Screw Mount (#8)	.89	.20 x .59/5.08 x 14.99	.45 x .59/11.43 x 14.99	100	1,000

· Natural nylon color.

*Synthetic Rubber Adhesive

Product Base is .94" x .94" (23.88 x 23.88 mm)

Hole for #6 screw

For adhesive-back bases, temperature rating is 32° F to 120° F (0° C to 48° C)

For non-adhesive-back bases, temperature rating is -40° F to 185° F (-40° C to 85° C)

Note: See product expiration date on packages with adhesive. Periodically check product for adhesion and replace as needed. Product is for wire management only and is not intended for use as a primary support of wire, cable, etc.

Simple to install!

Snap-In Mounting Base for Preassembled Ties



STD. PKG.	BULK PKG.	MOUNTING	MAX. TIE	LENGTH	WIDTH	MATERIAL	STD.	BULK
CAT. NO.	Cat. No.	METHOD	WIDTH ACCOM.	IN./MM	IN./MM		PKG. QTY.	PKG. QTY.
TC5353A	TC353A	SRA* Adhesive	.190	2.00/50.80	1.00/25.40	Nylon 6/6	25	500

Natural nylon color.

Temperature Rating: 32° F to 120° F (0° C to 48° C).

*Synthetic Rubber Adhesive.

Note: See product expiration date on package. Periodically check product for adhesion and replace as needed.

Product is for wire management only and is not intended for use as a primary support of wire, cable, etc.

Great for securing cables! Aluminum Mounting Plates



STD. PKG. CAT. NO.	MOUNTING METHOD	WIDTH ACCOM.	MAX. TIE Length Accom.	WIDTH IN./MM	MATERIAL	BULK PKG. QTY.
TC105	TC2PA/Screws	.190	1.00/25.40	.50/12.70	Aluminum	1,000
TC824-TB	TC2PA	.190	1.38/34.93	.38/.38	Aluminum	1,000
650-41349*	TC2PA/Screws	.190	1.38/34.93	.38/.38	Aluminum	1,000
650-41863	Adhesive	.190	1.38/34.93	.38/.38	Aluminum	1,000

Temperature Rating: 32° F to 150° F (0° C to 66° C). *650-4

*650-41349 has two holes for mounting.

Note: See product expiration date on package. Periodically check product for adhesion and replace as needed. Product is for wire management only and is not intended for use as a primary support of wire, cable, etc.

Super strong adhesive! Mounting Base Adhesive





STD. PKG		STD.
CAT. NO.	DESCRIPTION	PKG. QTY
TC2PA	Consists of one tube of adhesive and activator	1

Note: See product expiration date on package. Periodically check product for adhesion and replace as needed. Product is for wire management only and is not intended for use as a primary support of wire, cable, etc.



United States

Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354 Technical Services
Tel: 888.862.3289



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ABB manufacturer:

Other Similar products are found below:

TY27MX TV10-516R RF727 2CMA100178R1000 ACS150-01E-09A8-2 KS70-1104 A75-30-11-230V-50HZ 10-100 5SDD 92Z0401

ESV14-BS EZS-21-250 F204AC-40/0.1 F362-25/0.03 A40-30-10-84 AF26-30-00-14 AF30-30-00-13 AF460-30-11-68 AF50-30-11-70

1455 B14-250 EF45-30 ERG297 HSC2-20 ISAM201904R1001 ISAM350000R1003 ISAZ711201R1045 ISAZ721201R1009

1SAZ721201R1014 ISAZ721201R1025 ISAZ721201R1045 ISBL367001R1300 ISDA057197R1 ISFA611100R1104 ISFA611101R1002

1SFA611130R1103 ISFA611133R1106 ISFA611143R1101 ISFA611202R1108 ISFA611203R1108 ISFA611210R1101

1SFA611215R1001 ISFA611216R1108 ISFA611281R1002 ISFA611285R1002 ISFA611702R6006 ISFA616162R1025

ISFA896106R1100 ISVR730020R0200 IPC4111 OHB125J12