

ÖLFLEX® 150 CY

DB 0015703

valid from: 2014-03-11

Application

ÖLFLEX® 150 CY cables are oil resistant power and control cables designed for the European, North American and Canadian market, for occasional flexible use and fixed installation subject to normal mechanical load conditions. They are among others designed for use in dry, damp and wet rooms. Outdoor use: They may only be installed with UV protection and considering the temperature range. ÖLFLEX® 150 CY cables are increased oil resistant and at room temperature they are widely resistant to acids and caustic solutions. They are suitable for non-continuously recurring movement without tensile load. Continuous operational movements, restricted guidance, usage of these cables in moving cable carriers or on motor drum guidance or under a strain of more than 15 N/mm² are not allowed.

Application range: Plant engineering, industrial machinery, heating and air-conditioning systems

Application range:

plant engineering, industrial machinery, heating and air conditioning systems

HAR: DIN VDE 0298-300 resp. VDE 0298-300
 acc. to UL: PVC-sheathed cables for external interconnection or internal wiring of electric and electronic equipment, Use when getting in contact with oil not above +60 °C (60 °C oil rating)
 acc. CSA: CSA AWM I A/B II A/B, cables for internal or external interconnection with or without mechanical load

Design

Design ≤ 61 cores: acc. to EN 50525-2-51 resp. VDE 0285-525-2-51
 > 61 cores: based on EN 50525-2-51 resp. VDE 0285-525-2-51
 UL AWM Style 21098 or 2587, CSA C22.2 No. 210-11

Approvals UL AWM Style 21098 or 2587 (File No. E63634)
 CSA AWM I A/B II A/B (File No. LL 53776)
 ≤ 61 cores:
 acc. to H05VVC4V5 acc. to EN 50525-2-51 resp. VDE 0285-525-2-51
 > 61 cores:
 based on EN 50525-2-51 resp. VDE 0285-525-2-51

Conductor fine wire strands of bare copper, acc. to IEC 60228 resp. VDE 0295, Class 5

Core insulation PVC compound TI2 acc. to DIN EN 50363-3 resp. VDE 0207-363-3
 (UL/CSA 90°C rating)

Core identification acc. to VDE 0293-1, with or without GN/YE ground conductor
 black cores with white numbers acc. to DIN EN 50334 resp. VDE 0293-334

Inner sheath PVC compound TM 2 acc. to DIN EN 50363-4-1 resp. VDE 0207-363-4-1
 (UL/CSA 90°C rating)

Screen braid of tinned copper, coverage = 85 % (nominal value)

Outer sheath PVC compound TM5 acc. to DIN EN 50363-4-1 resp. VDE 0207-363-4-1
 (UL/CSA 90°C rating)
 colour: silver grey, similar RAL 7001

Electrical properties

Nominal voltage U₀/U in acc. to HAR: 300 / 500 V
 U acc. to UL / CSA: 600 V

Test voltage core / core 3000 V AC
 core / screen 3000 V AC

ÖLFLEX® 150 CY

DB 0015703

valid from: 2014-03-11

Mechanical and thermal properties

Min. bending radius	occasional flexing:	20 x outer diameter
	fixed installation:	6 x outer diameter
Temperature range	occasional flexing:	acc. to HAR -5 °C up to +70 °C max. conductor temp. acc. to UL / CSA -5 °C up to +90 °C max. conductor temp.
	fixed installation:	acc. to HAR -40 °C up to +70 °C max. conductor temp. acc. to UL / CSA -40 °C up to +90 °C max. conductor temp.
Oil resistance	TM 5 acc. to DIN EN 50363-4-1 resp. VDE 0207-363-4-1	
Flammability	HAR: acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2 UL: vertical flame test VW-1 CSA: FT1	
Tests	acc. to IEC 60811, EN 50395, EN 50396, UL 1581 and CSA 22.2	
EC-Directives	This cable is conform to the EC-Directives 2006/95/EC (Low Voltage Directive) and 2011/65/EG (RoHS, Restriction of the use of certain hazardous substances).	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[70002624](#) [70002668](#) [EPIC KIT H-A 10 BS TBF-LB M20](#) [EPIC KIT H-A 16 SS TS M20](#) [EPIC KIT H-A 3 BS AG](#) [EPIC KIT H-A 3 BS AGS](#)
[EPIC KIT H-BE 10 SS TS M25](#) [EPIC KIT H-BE 16 BS AG](#) [EPIC KIT LS1 A1 3+PE+4 K](#) [EPIC KIT LS1 F6 5+PE K](#) [22260044](#) [22260046](#)
[22260134](#) [22262020](#) [22262022](#) [22262023](#) [22262027](#) [21700623](#) [22260101](#) [22260123](#) [55506305](#) [52015800](#) [52220000](#) [EPIC KIT H-A 16 BS](#)
[SGR-LB M20](#) [EPIC KIT H-BE 10 BS TBF M25](#) [EPIC KIT H-BE 10 SS TG M25](#) [EPIC KIT LS1 F6 3+PE+4 K](#) [0021898](#) [0035832](#) [0049003](#)
[4520121](#) [52106220](#) [52107830](#) [53112160](#) [1136304 50M](#) [22260021](#) [AB-C4-7,5TPE-M12FS-HD](#) [AB-C3-10,0PUR-M8FA-2L](#) [AB-C4-M12MS-](#)
[2,0PUR](#) [71220132](#) [71220134](#) [71220136](#) [71220152](#) [73220126](#) [73220145](#) [73220160](#) [73220238](#) [52005770](#) [52107850](#) [53001050](#)