



### Heat Shrinkable Tubing adhesive lined

**EPS-300 - 3:1 shrink ratio**

**EPS-400 - 4:1 shrink ratio**

Heat shrinkable tubing EPS seals and protects a wide variety of electrical applications like back end connector sealing, connector-to-cable transitions and splices.

#### Features and Benefits

- Flexible, thin walled polyolefin heat shrink tubing
- With coextruded hot melt adhesive inner wall
- Protects against moisture
- Provides an environmental sealing of complex parts



PTA300 and PTA400 offer high shrink ratios and protection against humidity.



**Cut lengths available on request. Please contact us!**



Heat Shrinkable Tubing 3:1 with adhesive



Heat Shrinkable Tubing 4:1 with adhesive



<b>MATERIAL</b>	Polyolefin, cross-linked (PO-X)
<b>Operating Temperature</b>	-55 °C to +125 °C
<b>Minimum Shrink Temperature</b>	+120 °C
<b>Longitudinal change after shrinkage</b>	-10 % max.
<b>Softening Point Adhesive</b>	+90 °C
<b>Dielectric Strength</b>	15 kV/mm according to IEC 60684 P2
<b>Flammability</b>	ASTM D2671 (outer layer only)
<b>Specifications</b>	SAE - AMS - DTL-23053 / 4



TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Shrink Ratio	Article-No.
EPS-300-3/1	3.0	1.0	1.00	400 m	Black (BK)	3:1	340-03010
EPS-300-6/2	6.0	2.0	1.00	300 m	Black (BK)	3:1	340-06020
EPS-300-9/3	9.0	3.0	1.40	150 m	Black (BK)	3:1	340-09030
EPS-300-12/4	12.0	4.0	1.80	100 m	Black (BK)	3:1	340-12040
EPS-300-19/6	19.0	6.0	2.20	50 m	Black (BK)	3:1	340-19060
EPS-300-24/8	24.0	8.0	2.50	25 m	Black (BK)	3:1	340-24080
EPS-300-40/13	40.0	13.0	2.50	25 m	Black (BK)	3:1	340-40130

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Shrink Ratio	Article-No.
EPS-400-4/1	4.0	1.0	1.00	300 m	Black (BK)	4:1	341-04010
EPS-400-8/2	8.0	2.0	1.00	150 m	Black (BK)	4:1	341-08020
EPS-400-12/3	12.0	3.0	1.40	100 m	Black (BK)	4:1	341-12030
EPS-400-16/4	16.0	4.0	1.80	100 m	Black (BK)	4:1	341-16040
EPS-400-24/6	24.0	6.0	2.20	50 m	Black (BK)	4:1	341-24060
EPS-400-32/8	32.0	8.0	2.50	25 m	Black (BK)	4:1	341-32080

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval.

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR6145-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [617867N001](#) [6500750004](#) [D-306-38](#) [770-003S106W2](#) [770-007A303](#)  
[770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [MFT-MT2000-NO.14-0-SP](#) [MFT-MT2000-NO.65-X-SP](#)  
[MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#)  
[MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [FP301-3/8-6"-Clear](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#) [121-018-40](#) [121-123-1-1-32BTC](#) [121-123-1-1-40BTC](#) [121-127-09BK](#)