SIZE -----40W-----SPECIFICATIONS DRG. NO TD-40 MODEL 1100 稱: 輸 入 35 W NOMINAL INPUT POWER 最大許可輸入 45 W POWER HANDLING CAPACITY 商 阳 16  $\Omega \pm 15\%$  (Hz) VOICE COIL IMPEDANCE 低域階振週率 250-5000 Hz± HzRESONANT FREQUENCY 出 音 108 dB 以上 MEAN SOUND PRESSURE LEVEL 使 用 磁 鐵 100x60x15( gr oz) MAGNET SIZE 磁東 12000 GAUSS FLUX DENSITY 1070 gr. NET WEIGHT APPLICATIONS 客戶指示名稱 CUSTOMER NAME SCALE Potentiometer Range: 10 dB Rectifier: DM S Lower Lim. From: 10 18 dB DRAWN CHECKED 主 辦 Trevesed 客戶批准 APPROVED 500 1000 Zero Level: 60 Hz 2000 Hz 5000 Multiply Freq. Scale by \_\_ (1612/2112) A B C Lii

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for NTE manufacturer:

Other Similar products are found below:

747 797 868 1724 NEH680M50FE NEHH1.0M450CB NTE526A 228A 231 954 2023 510 WH20-04-25 04-SLPE3750A 5615 591 69-36WW-WR-KIT 7056 7448 NEH.10M50AA NEH2.2M63AA NEH330M35DD NEH33M10AA NEV.22M100AA NEV470M50FF NTE133 NTE542 NTE74154 R02-11A10-120H 04-SCBW25L-BK 04-SCBW6C-BK 04-SCBW32L-BK 04-SCW10C-BK 04-SCBW19L-GR 04-SCW19L-WH 04-SCW19L-OR 04-SCW38L-WH 04-SCBW50L-OR 04-SCBW50L-GR 04-SCW10C-GR 04-SCW10C-OR 04-SCW10C-OR 04-SCBW32L-GR 04-SCBW32L-WH 04-SCBW32L-OR 04-SCBW6C-WH 04-SCBW6C-GR 04-SCBW6C-OR 04-SCBW25L-GR 04-SCBW25L