

## **EUR-44-00** Industrial transmission adapter USB - RS485 with galvanic isolation.



The EUR-44-00 is industrial transmission adapter USB  $\leftrightarrow$  RS485 with galvanic isolation and own independent power supply. EUR-44-00 contains FTDI FT232 chip (USB to UART), which handles all USB signalling and protocols. On the one hand, has a mini-USB input, the second connector A / B. The integrated electronics also include RS485 transceiver, Tx and Rx LEDs which give a visual indication of traffic on cable. The EUR-44-00 can be USB powered or power supply AC/DC and USB 2.0 full speed compatible.

## Technical data:

Transmission speed 115kbit/s

EIA/TIA-485 communication interface with low power requirements

Power supply voltage: 110/240V AC

Power consumption: <0,2A</li>

Electronic supply voltage: 5V DC

Operating temperature: -25°C ÷ 50°C

Casing protection grade: IP20

Protection type of housing class: 2

Cable length of 1.5m (5feet)

Dimensions: 75x45x28 mm



## Set contains:

- Adapter USB ↔ RS485
- USB cabels
- Power supply AC/DC

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Controllers category:

Click to view products by NOVASTER manufacturer:

Other Similar products are found below:

CS1WCN223 CS1WCN713 CS1WKS001E 61F-11NH 61FGPN8DAC120 61F-GP-NT AC110 61F-GPN-V50-AC110 70177-1011 F03-03

HAS B F03-03 HAS C F03-31 81513201 81513535 81550401 FT1A-C12RA-W 88981106 H2CAC24A R88A-CAGA005S R88A
CRGB003CR-E R88ARR080100S R88A-TK01K DCN1-1 DTB4896VRE DTB9696CVE DTB9696LVE MR-50LF+ E53-AZ01 E53E8C

E5CWLQ1TCAC100240 B300LKL21 NE1ASCPU02EIPVER11 NE1SCPU01 NE1SDRM21U NSCXDC1V3 NSH5-232CW-3M

NT20SST122BV1 NV3Q-SW41 NV4W-ATT01 NV-CN001 OAS-160-N K31S6 K33-L1B K3TX-AD31A L595020 SRS2-1 G32X-V2K

26546803 26546805 26546831 CJ1W-OD204