

Contact Tachometer



Plus Linear surface speed measurements in ft/min or m/min

Features:

- · Large 5 digit LCD display is easy to read
- Built-in memory recalls last MAX/MIN value stored
- Autoranging with 0.05% accuracy
- Contact measurements from 0.5 to 19,999rpm plus linear surface speed measures in ft/min or m/min
- Simply contact rotating object with sensor tip and read
- Accessory wheels enable tachometer to measure linear surface speeds
- Complete with cone tip, flat tip and spare wheel for surface speed measurements, four 1.5V AA batteries and case



Accessory wheels enable tachometer to measure linear speed surfaces



Specifications	
Range	0.5 to 19,999rpm
	0.2 to 6560ft/min
	0.05 to 1999.9m/min
Accuracy	$\pm (0.05\% \text{rdg} + 1\text{d})$
Sampling Time	1sec>6rpm
Resolution	0.1rpm (0.5 to 999.9rpm);1rpm >1000rpm
Dimensions	6.7 x 2.8 x 1.5" (170 x 27 x 37mm)
Weight	9.2oz (260g)

Ordering Information:

461891	Contact Tachometer
461891-NIST	461891 with NIST certificate
461899	Set of Spare Wheels
461936	Spare Reflective Tape (5pks, 23" each roll)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Counters & Tachometers category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

LC2H-FE-2K-N H7CN-XLN DC12-48 LC24-F-N H7CXAWD1NDC1224AC24 H7ER-NV1-H H7CX-A114S-N AC100-240 H7CX-AWSD-N-DC12-24 H7CX-AU-N AC100-240 GPMZC-SET CX6S-1P2F CX6S-1P4F CX6S-2P2F CX6S-2P4F H127.010A01H H5KLR-11 100-240V AC/DC H7CX-AUD1-N H7CX-AW-N 3.550.401.075 3.550.401.351 LC2H-C-2K-N LC2H-C-30-N LC2H-F-DL-2KK LC4H-R4-AC240VS LC4H-R6-AC240V 1.150.510.012.550 1.150.510.054.550 1.150.510.056.550 6.520.012.300 6.560.010.300 SLE-73-1400-1-4-01 SLIK-94-1521-1-3-001 SLN-94-1421-1-3 SPI-73-1411-1-3-011 CT6S-1P4 Y-50 LC4H-R4-AC24V LC4H-R4-DC24V CT6S-2P4 LC2H-F-DL-2KK-B LC2H-FE-DL-2KK-B LC2H-FE-FV-30 H127.010A01G H5KLR-8B 12-48 AC/DC H7CX-A11-N H7CX-AD-N H7CX-AU-N H7ER-NV1 H8DA 12-48V AC/DC 87622062 99776901