

# Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output	
<b>30 mm - Embeddable, eurofast<sup>+</sup> Connection</b> 	Bi 10-M30-AD4X-H1141	T4417500		10	2-Wire DC	
	Bi 12-M30-AD4X-H1141	T4417041	<b>Extended Range</b>	12		
	Bi 10U-M30-AD4X-H1144	M4405072	<b>uproxx+</b>	10		
	Bi 10-M30-AN6X-H1141	T4617600			10	3-Wire DC NPN
	Bi 10U-EM30-AN6X-H1141	M1636350	<b>Uprox</b>	10		
	Bi 10U-EM30H-AN6X2-H1141	M1636407	<b>Uprox, Stoneface</b>	10		
	Bi 10U-EM30H-AN6X2-H1141/S1589	M1636490	<b>weldguard<sup>+</sup>, Uprox</b>	10		
	Bi 10U-M30-AN6X-H1141	M1636150	<b>Uprox</b>	10		
	Bi 15-M30-AN6X-H1141	T4618600	<b>Extended Range</b>	15		
	Bi 15-EM30H-AN6X-H1141	T4618692	<b>Stoneface, Ext. Range</b>	15		
	Bi 15U-M30-AN6X-H1141	M1636736	<b>Uprox+</b>	15		
	Bi 10-M30-AP6X-H1141	T4617500			10	3-Wire DC PNP
	Bi 10U-EM30-AP6X-H1141	M1636340	<b>Uprox</b>	10		
	Bi 10U-EM30H-AP6X2-H1141/S1589	M1636491	<b>weldguard, Uprox</b>	10		
	Bi 10U-M30-AP6X-H1141	M1636140	<b>Uprox</b>	10		
	Bi 10U-M30-AP6X2-H1141	M1636145	<b>Uprox</b>	10		
	Bi 15-M30-AP6X-H1141	T4618500	<b>Extended Range</b>	15		
	Bi 15-EM30H-AP6X-H1141	T4618592	<b>Stoneface, Ext. Range</b>	15		
	Bi 15-EM30H-AP6X-H1141/S1589	T4618593	<b>weldguard</b>	15		
	Bi 15U-EM30-AP6X-H1141	M1636733	<b>uproxx+</b>	15		
	Bi 15U-M30-AP6X-H1141	M1636732	<b>Stainless steel uproxx+</b>	15		
	<b>30 mm - Embeddable, eurofast<sup>+</sup> Connection</b> 	Bi 15-EM30H-AP6X-H1141/S1610	T4618589	<b>Weld/armorguard</b>	15	3-Wire DC PNP
	<b>30 mm - Embeddable, eurofast<sup>+</sup> Connection</b> 	Bi 10-M30-VN4X-H1141	T1571600	<b>Comp. Outputs</b>	10	4-Wire DC NPN
		Bi 10U-M30-VN4X-H1141	M1582352	<b>Uprox, Comp. Outputs</b>	10	
		Bi 15-M30-VN4X-H1141	T4570711	<b>Comp. Outputs</b>	15	
Bi 10-M30-VP4X-H1141		T1561600	<b>Comp. Outputs</b>	10	4-Wire DC PNP	
Bi 10U-M30-VP4X-H1141		M1582253	<b>Uprox, Comp. Outputs</b>	10		
Bi 15-M30-VP4X-H1141		T4570710	<b>Comp. Outputs</b>	15		
Bi 10-M30-Y1X-H1141		M4020200			10	2-Wire DC

For detailed sensor specifications see Section M.  
 Normally Closed versions available upon request, consult factory.



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	Power LED	Output LED	Mating Cordset	Wiring Diagram #	Wiring Diagrams
10-65 VDC	500	≤100	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.2T-*	1	<b>Diagram 1</b> 
	500	≤100	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.2T-*	1	
	1000	≤100	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	2	
10-30 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	<b>Diagram 2</b> 
	2000	≤200	-30 to +85	IP 68	SS	PA 12	N/A	YE	RKV 4T-*	3	
	2000	≤200	-30 to +85	IP 68	SS	SF	GN	YE	RKV 4T-*	3	
	2000	≤200	-30 to +85	IP 68	SS	WG	GN	YE	RKC 4T-*/S1587	3	
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	
	300	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	
	300	≤200	-25 to +70	IP 67	SS	SF	N/A	YE	RKC 4T-*/S1587	3	
750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	3		
10-30 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	4	<b>Diagram 3</b> 
	2000	≤200	-30 to +85	IP 68	SS	PA 12	N/A	YE	RKV 4T-*	4	
	2000	≤200	-30 to +85	IP 68	SS	WG	GN	YE	RKC 4T-*/S1587	4	
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	4	
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	GN	YE	RK 4T-*	4	
	300	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	4	
	300	≤200	-25 to +70	IP 67	SS	SF	N/A	YE	RKV 4T-*	4	
	300	≤200	-25 to +70	IP 67	SS	WG	N/A	YE	RKC 4T-*/S1587	4	
	750	≤200	-30 to +85	IP 68	SS	LCP	N/A	YE	RK 4T-*	4	
10-30 VDC	300	≤200	-25 to +70	IP 67	AG	WG	N/A	YE	RKC 4T-*/S1587	4	<b>Diagram 4</b> 
	750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	4	
10-30 VDC	300	≤200	-25 to +70	IP 67	AG	WG	N/A	YE	RKC 4T-*/S1587	4	<b>Diagram 5</b> 
	750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	4	
10-65 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5	<b>Diagram 6</b> 
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5	
	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5	
10-65 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	6	<b>Diagram 7</b> 
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	6	
	300	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	6	
5-30 VDC	2000	Remote	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.21T-*	7	

Barrels

\* Length in meters.

For material descriptions see page M36.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Turck manufacturer](#):*

Other Similar products are found below :

[BI10-M30-AP6X-H1141](#) [BI2-G12-AZ33X-7M](#) [BS4151-0/13.5](#) [NI12U-G18-ADZ30X2-B1331](#) [NI12U-M18-AN4X](#) [BI1.5-G08K-AN6X](#) [BI5-G18-AZ3X](#) [BI5-G18-AZ3X-B1331-50MM](#) [VB20](#) [BMWS 8151-0/9](#) [NI4U-EG08-AN6X-H1341](#) [BC 5-Q08-AP6X2-V1131](#) [NI5-G12-AP6X-H1141](#) [NI14-G18-ADZ30X2](#) [BI5-G18-Y0](#) [C2-A20DX/024VDC](#) [NI35U-CK40-ADZ30X2-B3131](#) [W/BS4](#) [RK40-2M](#) [BI5-G18-AP6X-B1441/S34](#) [RSM FKM RKM 57](#) [BC5-S18-Y1X](#) [FEN20-4DIP-4DXP-DIN](#) [BCF5-S18-RP4X/S90](#) [BI5-M18-AZ3X/S120](#) [BI2-G08-AN6X](#) [NI12U-MT18-AP4X-H1141](#) [BI8U-Q10-AP6X2-V1131](#) [CT 2-A30/M](#) [PT-30HG-13-LI3-H1131](#) [FCS-N1/2A4P-AP8X-H1141](#) [B1N360V-Q20L60-2LU3-H1151](#) [CMBS 8141-0](#) [BI10-M30-AN6X-H1141](#) [CMB 8151-0](#) [RK 4.5T-10](#) [VB80-P7X9-8/CS12](#) [NI12U-M18-AP6X-H1141](#) [RK 4T-6](#) [BS 4131-0/9](#) [B 4241-0/9](#) [NI3-EG08K-Y1-H1341](#) [RK 4.4T-10](#) [RI360P0-QR24M0-INCRX2-H1181](#) [BI10U-Q14-AP6X2-V1131](#) [FDN20-4S-4XSG-E](#) [FKV-CC](#) [FSFD 8](#) [NI4U-EG08-RP6X-V1131](#) [RK 4.4T-8](#) [NI8-M18E-VN4X](#)