



## Flexible Cable Support

### Heladuct Flex

Heladuct flexible cable supports are commonly used in switching cabinets. They are also used in the furniture industry, where cables need to be routed rapidly and attractively.

#### Features and Benefits

- Space-saving wiring system
- Highly flexible, can be installed at angles of 90° and higher
- Cable clearly open to view
- Rapid mounting with screws or adhesive strip with high-quality foam bonding layer



Heladuct Flex- clearly and space-saving arrangement of wiring, even at angles above 90°.

<b>MATERIAL</b>	Polypropylene (PP)
<b>Operating Temperature</b>	-20 °C to +70 °C
<b>Adhesive</b>	Synthetic rubber with base of polyethylene foam
<b>Flammability</b>	UL94 V0 (excluding adhesive)



TYPE	Nominal Ø	No. of Wires			Max. load on a length of 500 mm at 70 °C (g)	Colour	Length (L)	Article-No.
		9 x 0.75 mm <sup>2</sup>	6 x 1.50 mm <sup>2</sup>	4 x 2.50 mm <sup>2</sup>				
Heladuct Flex10	10	9 x 0.75 mm <sup>2</sup>	6 x 1.50 mm <sup>2</sup>	4 x 2.50 mm <sup>2</sup>	100	White (WH)	500.0	164-11008
Heladuct Flex20	20	32 x 0.75 mm <sup>2</sup>	22 x 1.50 mm <sup>2</sup>	14 x 2.50 mm <sup>2</sup>	300	White (WH)	500.0	164-21008
Heladuct Flex30	30	67 x 0.75 mm <sup>2</sup>	50 x 1.50 mm <sup>2</sup>	34 x 2.50 mm <sup>2</sup>	650	White (WH)	500.0	164-31008
Heladuct Flex40	40	-	81 x 1.50 mm <sup>2</sup>	60 x 2.50 mm <sup>2</sup>	1,100	White (WH)	500.0	164-41008

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.

### Heladuct Flex with Adhesive

TYPE	Nominal Ø	No. of Wires			Max. load on a length of 500 mm at 70 °C (g)	Colour	Length (L)	Article-No.
		9 x 0.75 mm <sup>2</sup>	6 x 1.50 mm <sup>2</sup>	4 x 2.50 mm <sup>2</sup>				
Heladuct Flex10SK	10	9 x 0.75 mm <sup>2</sup>	6 x 1.50 mm <sup>2</sup>	4 x 2.50 mm <sup>2</sup>	100	White (WH)	500.0	164-11108
Heladuct Flex20SK	20	32 x 0.75 mm <sup>2</sup>	22 x 1.50 mm <sup>2</sup>	14 x 2.50 mm <sup>2</sup>	300	White (WH)	500.0	164-21108
Heladuct Flex30SK	30	67 x 0.75 mm <sup>2</sup>	50 x 1.50 mm <sup>2</sup>	34 x 2.50 mm <sup>2</sup>	500	White (WH)	500.0	164-31108
Heladuct Flex40SK	40	-	81 x 1.50 mm <sup>2</sup>	60 x 2.50 mm <sup>2</sup>	400	White (WH)	500.0	164-41108

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Non-Heat Shrink Tubing and Sleeves](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CTA-0053](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-123-06](#) [120-123-10](#) [120-125-12BL](#) [120-125-12R](#) [120-125-20R](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#) [120-105-1-1-06BE](#) [120-105-1-1-06CE](#) [120-116-1-1-06BP](#) [120-116-1-1-10BP](#) [120-116-1-1-12BF](#) [120-123-12](#) [120-125-09](#) [120-125-12](#) [120-125-12Y](#) [120-125-52BL](#) [120-S002-12](#) [HC1B-7008-0375-0](#) [120-S001-09](#) [120-S002-09](#) [121-101-1-1-56BFC](#) [121-101-1-1-64BFC](#) [RAY-90-3.0\(100\)](#) [20675-2](#) [8S42-100FR-CS8184](#) [SAS-115-1-1048-1X](#) [SAS-160-1-1048-1X](#) [25T-GB](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [3-1991136-0](#) [561-SL1000NYGY](#) [561-SL1000PP](#) [561-SL250FRPP](#)