

TECHNICAL DATA

# Fluke 1630-2 Earth Ground Clamp



## Stakeless earth ground loop and ac leakage current clamp for fast, safe indoor/outdoor earth ground resistance and ac leakage current tests.

Test the grounding components of equipment in hard-to-reach spaces, including areas that are indoors or fully paved and do not permit driving auxiliary test stakes. Stay on line—identify ground loop resistance without the need to disconnect then reconnect the earth electrode from the system.

The Fluke 1630-2 Stakeless Earth Ground Clamp is the kind of high-quality, rugged tool you expect from Fluke. Heavy-duty clamp jaw stays in alignment and in calibration even in every day, on-the-job industrial environments.

### Stakeless measurement

The 1630-2 clamp measures earth ground loop resistances for multi-grounded systems using the dual-clamp jaw. This test technique eliminates the dangerous and time-consuming activity of disconnecting parallel grounds, as well as the process of finding suitable locations for auxiliary test stakes. You can also perform ground tests in places that were previously difficult: inside buildings, on power pylons or anywhere you don't have access to soil to place auxiliary test stakes.

With this test method, a two-process measurement is made around the earth ground wire or bus bar using the specially-designed jaw of the 1630-2 clamp. Auxiliary test stakes are not used at all. A known voltage is induced by the source in the clamp, and the current is measured by the sensor in the clamp. The tester automatically determines the earth loop resistance for this section of the earthing system.

### AC LEAKAGE CURRENT MEASUREMENT

Identify ac leakage currents without disconnecting the earth ground stake from the grounding system—ideal for system troubleshooting.

### RUGGED

Heavy-duty clamp jaw stays in alignment and in calibration even in every day, on-the-job industrial environments.

### LOGGING MEASUREMENTS

The earth ground clamp saves time by automatically recording data at pre-set intervals and saves up to 32,760 measurements in memory at the set logging interval. Saves time by recording and storing measured values.

### ALARM THRESHOLD

User-defined high/low alarm limits, for rapid measurement evaluation.

### BAND-PASS FILTER

Selectable band-pass filter function removes unwanted noise from the ac leakage current measurement.

## Specifications

Electrical specifications			
Maximum voltage to earth ground	1000 V		
Battery type	4 x 1.5 V AA alkaline IEC/EN LR6		
Battery life	More than 15 hours*		
Frequency range	40 Hz to 1 kHz		
Ingress protection	IEC/EN 60529: IP30 with jaw closed		
LCD	Digital reading	9999 counts	
	Refresh rate	4/s	
Temperature	Operating	-10 °C to +50 °C (14 °F to +122 °F)	
	Storage	-20 °C to +60 °C (-4 °F to +140 °F)	
Operating humidity	Non condensing (<10 °C) (< 50 °F)		
	≤90 % RH (at 10 °C to 30 °C [50 °F to 86 °F])		
	≤75 % RH (at 30 °C to 40 °C [86 °F to 104 °F])		
	≤45 % RH (at 40 °C to 50 °C [104 °F to 122 °F]) (Non condensing)		
Altitude	Operating	2000 m (6561 ft.)	
	Storage	12,000 m (39370 ft.)	
Reference temperature	23 °C ±5 °C (73 °F ±9 °F)		
Temperature coefficient	0.15 % X (specified accuracy)/ °C (<18 °C or >28 °C [(<64.4 °F or >82.4 °F)])		
Overload indication	OL		
Display Reading Specification with Loop Resistance Standard	Input (Ω)	Minimum	Maximum
	0.474	0.417	0.531
	0.5	0.443	0.558
	10	9.55	10.45
	100	96	104.0
Data logging capacity	Minimum of 32,760 measurements		
Data logging interval	1 second to 59 minutes and 59 seconds		
Safety	General	IEC/EN 61010-1: Pollution Degree 2 IEC/EN 61557-1	
	Measurement	IEC/EN 61010-2-032: CAT IV 600 V / CAT III 1000 V	
Current clamp for leakage current measurements	IEC/EN 61557-13: Class 2, ≤30 A/m		
Resistance to Earth	IEC/EN 61557-5		
Effectiveness of the protective measures	IEC/EN 61557-16: cutoff frequency 20 kHz (-3 dB)		
Electromagnetic compatibility (EMC)	International	IEC/EN 61326-1: Portable Electromagnetic Environment CISPR 11: Group 1, Class B, IEC/EN 61326-2-2	
	Korea (KCC)	Class A equipment (Industrial Broadcast & Communications Equipment)	
	USA (FCC)	47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103.	

\* In Ground Resistance measurement mode, with backlight turned off, and RF mode turned off

General specifications	
Conductor size	40 mm (1.57 in) approximately
Dimensions (L x W x H)	283 mm x 105 mm x 48 mm (11.1 in x 4.1 in x 1.9 in)
Weight	880g (31 oz)
Warranty	One year

**Earth ground loop resistance**

Range	Accuracy [1] (± % of reading + Ω)
0.025 Ω to 0.249 Ω	1.5% + 0.02 Ω
0.250 Ω to 0.999 Ω	1.5% + 0.05 Ω
1.000 Ω to 9.999 Ω	1.5% + 0.10 Ω
10.00 Ω to 49.99 Ω	1.5% + 0.30 Ω
50.00 Ω to 99.99 Ω	1.5% + 0.50 Ω
100.0 Ω to 199.9 Ω	3.0% + 1.0 Ω
200.0 Ω to 399.9 Ω	5.0% + 5.0 Ω
400 Ω to 599 Ω	10.0% + 10 Ω
600 Ω to 1500 Ω	20.00%

[1] Loop resistance with no inductance, conductor centered and perpendicular to jaw.

**Earth ground leakage current mA**

Autorange 50/60 Hz, True rms, crest factor CF ≤3

Range	Resolution	Accuracy [1]
0.200 mA to 3.999 mA	1 μA	±2.0 % rdg ±0.05 mA
4.00 mA to 39.99 mA	10 μA	±2.0 % rdg ±0.03 mA
40.0 mA to 399.9 mA	100 μA	±2.0 % rdg ±0.3 mA
0.400 A to 3.999 A	1 mA	±2.0 % rdg ±0.003 A
4.00 A to 39.99 A	10 mA	±2.0 % rdg ±0.030 A

[1] Applies to signal frequency  
 \* 40 Hz to 1 kHz with filter set to OFF  
 \* 40 Hz to 70 Hz with filter set to ON



**Ordering information**

**FLUKE-1630-2** Earth Ground Loop and Leakage Clamp

**Included**

Earth Ground clamp, hard case, loop resistance standard, 4 AA batteries, safety information guide and quick reference guide

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
 PO Box 9090, Everett, WA 98206 U.S.A.

**Fluke Europe B.V.**  
 PO Box 1186, 5602 BD  
 Eindhoven, The Netherlands

**For more information call:**  
 In the U.S.A. (800) 443-5853 or  
 Fax (425) 446-5116  
 In Europe/M-East/Africa +31 (0) 40 2675 200 or  
 Fax +31 (0) 40 2675 222  
 In Canada (800)-36-FLUKE or  
 Fax (905) 890-6866  
 From other countries +1 (425) 446-5500 or  
 Fax +1 (425) 446-5116  
 Web access: <http://www.fluke.com>

©2013, 2016-2017 Fluke Corporation.  
 Specifications subject to change without notice.  
 1/2017 2791074c-en

**Modification of this document is not permitted without written permission from Fluke Corporation.**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Clamp Multimeters & Accessories](#) category:*

*Click to view products by [Fluke](#) manufacturer:*

Other Similar products are found below :

[I800](#) [FLUKE 1630-2](#) [ZAPDUMOD-03](#) [ZARKMS-01-99](#) [UT233](#) [TESTO 770-3](#) [0590 7703](#) [AX-3550](#) [AX-M266C](#) [BM079](#) [BM089](#) [BM157](#)  
[BM162](#) [BM197](#) [KEW2210R](#) [FLUKE 80I-110S](#) [FLUKE I200](#) [FLUKE I200S](#) [FLUKE I3000FLEX-24](#) [FLUKE I310S](#) [FLUKE I400](#) [CIE600](#)  
[TESTO 770-2](#) [0590 7702](#) [34194A](#) [KEW2433R](#) [KEW8112](#) [FLUKE 772](#) [380976-K](#) [MA3110](#) [MA440](#) [MA443](#) [MA445](#) [FLUKE-374 FC](#)  
[TA74](#) [AMP-320](#) [CM55](#) [CM46](#) [I200](#) [ACD-6 PRO](#) [FLUKE-1630-2FC](#) [I410](#) [CM44](#) [CM42](#) [FLK-A3000 FC](#) [FLUKE-376 FC](#) [ACD-14-PRO](#)  
[MA610](#) [F201](#) [F205](#) [MA193 \(250 MM\)](#) [DIGIFLEX 4000A 350MM](#)