717/718/718Ex Pressure Calibrators









Fluke 718Ex





Fluke 717

Included Accessories

Fluke 717: Yellow Holster (H8OM excl. TPAK), TL75 Test Leads and AC72 Alligator Clips, Single 9V alkaline battery (two 9V batteries in 718), Instructions. 718/718Ex: 718: Yellow Holster, 718Ex: Red Ex Holster, TL75 Test Leads and AC72 Alligator Clips, two 9V batteries, user manual on CD-ROM.

Ordering Information

| Fluke 718 1G | Pressure Calibrator |
|------------------|---------------------|
| Fluke 718 30G | Pressure Calibrator |
| Fluke 718 100G | Pressure Calibrator |
| Fluke 718 300G | Pressure Calibrator |
| Fluke 718Ex 30G | Intrinsically Safe |
| | Pressure Calibrator |
| Fluke 718Ex 100G | Intrinsically Safe |
| | Pressure Calibrator |
| Fluke 717 1G | Pressure Calibrator |
| Fluke 717 30G | Pressure Calibrator |
| Fluke 717 100G | Pressure Calibrator |
| Fluke 717 300G | Pressure Calibrator |
| Fluke 717 500G | Pressure Calibrator |
| Fluke 717 1000G | Pressure Calibrator |
| Fluke 717 1500G | Pressure Calibrator |
| Fluke 717 3000G | Pressure Calibrator |
| Fluke 717 5000G | Pressure Calibrator |
| | |

Pump up the pressure

717 pressure Calibrators

- Measure pressure, 0.05% of full scale with internal sensor
- 1/8 NPT pressure fitting
- Compatible with non-corrosive gasses and liquids
- Pressure measurement to 700 bar using any of the Fluke-700Pxx Pressure Modules
- Wide range of selectable measurement units for pressure
- Current measurement with 0.015% accuracy and 0.001mA resolution
- Simultaneous pressure and current measurement for easy P/I or I/P testing
- 24 volt loop power supply
- Zero, Min-Max, Hold and Damping functions
- Pressure switch test captures set, reset and deadband values

718 Pressure Calibrators

- Same features as Fluke 717 plus
- Newly designed built-in pressure/vacuum hand pump with vernier and bleed valve helps protect the pump from damage and is easier to clean

718Ex 30G and 100G Intrinsically Safe Pressure Calibrator

- Same features as Fluke 718 (excl. loop supply)
- For use in explosion endangered areas
- ATEX certified (II 1G EEx ia IIC T4)
- Compatible with eight intrinsically safe pressure modules

Specifications

| Model | Range | Resolution | Over Pressure |
|-----------|-------------------------|------------|-------------------------------|
| 718 1G | -68.9 mbar to 68.9 mbar | 0.001 mbar | Over Pressure 5xFS |
| 718 30G | -850 mbar to 2 bar | 0.1 mbar | Over Pressure 2xFS |
| 718 100G | -850 mbar to 7 bar | 0.1 mbar | Over Pressure 2xFS |
| 718 300G | -850 mbar to 20 bar | 1 mbar | Over Pressure 375 PSI, 25 bar |
| 717 1G | -68.9 mbar to 68.9 mbar | 0.001 mbar | Over Pressure 5xFS |
| 717 30G | -850 mbar to 2 bar | 0.1 mbar | Over Pressure 2xFS |
| 717 100G | -850 mbar to 7 bar | 0.1 mbar | Over Pressure 2xFS |
| 717 300G | -850 mbar to 20 bar | 1 mbar | Over Pressure 375 PSI, 25 bar |
| 717 500G | 0 mbar to 34.5 bar | 1 mbar | Over Pressure 2xFS |
| 717 1000G | 0 mbar to 69 bar | 1 mbar | Over Pressure 2xFS |
| 717 1500G | 0 bar to 103.4 bar | 0.01 bar | Over Pressure 2xFS |
| 717 3000G | 0 bar to 207 bar | 0.01 bar | Over Pressure 2xFS |
| 717 5000G | 0 bar to 345 bar | 0.01 bar | Over Pressure 2xFS |

For Fluke 717/718 models: Supported Pressure Units; psi, in. $H_2O(4^\circ C)$, in. $H_2O(20^\circ C)$, cm $H_2O(4^\circ C)$,

cm $H_2O(20^{\circ}C)$, bar mBar, kPa, inHg, mmHg, kg/cm² Functions: Zero, Min, Max, Hold, Damp functions

Max. Voltage: 30 V

Operating temperature: -10°C to 55°C Safety: CSA C22.2 No. 1010.1:1992

EMC: EN50082-1:1992 and EN55022:1994 Class B Fluke 717: For use with non corrosive gasses and liquids

Fluke 718: For use with non corrosive gasses

717

Size (HxWxD): 201 mm x 98 mm x 52 mm

Weight: 0.6 kg

Warranty: Three years

718/718Ex

Size (HxWxD): 216 mm x 94 mm x 66 mm

Weight: 0.992 kg Warranty 718: Three years Warranty 718Ex: One year

Recommended Accessories

(Not for hazardous zones)







C125 (717) See page 84



80PK-27 See page 82



700P27 See page 71



700LTP See page 71

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Calibration Equipment category:

Click to view products by Fluke manufacturer:

Other Similar products are found below:

A25E-0030 AX-C830 AKT7113100 AKT8R111200 AKT8R112100 AKT8R112200 AKT4R1112001 AKT4R1121001 AKT4R1122001

12890 461950 AR604/P CLS 4-20MA 461750 461825 461830 461891 AX-C800 AX-C850 RT-820 FLUKE-805 AKT4R111100

AKT4R111200 AKT4R112100 AKT4R112200 AKT7111100J AKT7211100J AKT7212100J AKT7213100 AKT8R111100 REF2510R

K39-LCRR 350456 CAL73 412355A 412400 461831 461893 461895 461920 461995 480400 480403 HD780 PRC10 PRC15 PRC20

RPM40 FLUKE 707 FLUKE-715