

## SILVYN® FPAG-M

SILVYN® FPAG-M - conduit fitting for SILVYN® FPAS



Variety of approval certifications



Temperature-resistant



Optimum strain relief



Assembly time



Maximum vibration protection



Halogen-free

### Benefits

Fast assembly  
High-tensile  
Sealing  
Vibration protection

### Application range

In combination with protective conduit:  
SILVYN® FPAS  
Applications with strong vibrations

## SILVYN® FPAG-M

### Product features

In black colour UV-resistant and weather-proofed  
Removeable with a screwdriver

### Norm references / Approvals

UL FILENUMBER E308201

### Product Make-up

Metric connection thread  
Upper part with integrated all-round tothing

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001176 ETIM 5.0 Class-Description: Screw connection for corrugated plastic hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001176 ETIM 6.0 Class-Description: Screw connection for corrugated plastic hose
Certifications:	IEC EN 61386-23
Colour delivered:	Grey (RAL 7031) Black (RAL 9005), UV-resistant
Material:	PA66 Halogen-free
Protection rating:	IP 66
Temperature range:	-50°C to +135°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Metric size	For conduit with outer Ø (mm)	Suitable
SILVYN® FPAG-M black			
55506305	12 x 1.5	10	10
55506315	16 x 1.5	13	13
55506325	16 x 1.5	15.8	16
55506335	20 x 1.5	15.8	16
55507055	20 x 1.5	18.5	18
55506345	20 x 1.5	21.2	21
55506355	25 x 1.5	28.5	28
55506365	32 x 1.5	34.5	34
55506375	40 x 1.5	42.5	42
55506385	50 x 1.5	42.5	42
55506395	50 x 1.5	54.5	54
55506405	63 x 1.5	54.5	54
55506475	63 x 1.5	67.2	67
SILVYN® FPAG-M grey			
55506300	12 x 1.5	10	10
55506310	16 x 1.5	13	13
55506320	16 x 1.5	15.8	16
55506330	20 x 1.5	15.8	16
55507050	20 x 1.5	18.5	18
55506340	20 x 1.5	21.2	21
55506350	25 x 1.5	28.5	28
55506360	32 x 1.5	34.5	34
55506370	40 x 1.5	42.5	42
55506380	50 x 1.5	42.5	42
55506390	50 x 1.5	54.5	54
55506400	63 x 1.5	54.5	54
55506470	63 x 1.5	67.2	67

Last Update (01.01.2018)  
 ©2018 Lapp Group - Technical changes reserved  
 Product Management [www.lappkabel.de](http://www.lappkabel.de)  
 You can find the current technical data in the corresponding data sheet.  
 PN 0456 / 02\_03.16

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Conduit Fittings & Accessories](#) category:*

*Click to view products by [Lapp Kabel](#) manufacturer:*

Other Similar products are found below :

[S53.35A](#) [260-416](#) [DM0240-1/2A](#) [817.612.0](#) [55506625](#) [1.511.2001.50](#) [1.533.1601.50](#) [1.533.2001.50](#) [52005810](#) [817.716.0](#) [712.015.0](#) [216-420](#) [2276](#) [2663-P](#) [C2070-P](#) [3582V](#) [2643-P](#) [4975](#) [2644-P](#) [90480](#) [2404-P](#) [1047561](#) [2723-P](#) [55506355](#) [1.513.1101.14](#) [55502461](#) [55502462](#) [55502463](#) [55502464](#) [55502473](#) [166-22214](#) [166-22215](#) [166-24800](#) [166-25801](#) [166-30318](#) [SHR-C1](#) [2037 12-20 LGR](#) [2037 16-24 LGR](#) [HP50SS](#) [55502470](#) [SH PA6 BL ND10](#) [5308 946](#) [295.012.0](#) [2955 M16](#) [2955 M25](#) [2955 M32](#) [2955 M40](#) [297.212.0](#) [297.240.0](#) [298.012.0](#)