

## ÖLFLEX® HEAT 180 C MS

Screened and approved silicone cables for North America (AWM recognized)

ÖLFLEX® HEAT 180 C MS - shielded silicone power and control cable, UL/cUL-AWM approved for machine and plant construction in North America, suitable for +180 °C

### Info

MS = Multi-Standard

For use in the USA and Canada

UL AWM Style 4476 (150 °C/600 V)

Metric flexible conductor design



UV-resistant



Temperature-resistant



Interference signals



Halogen-free



Cold-resistant

### Benefits

Certified for the USA and Canada for export-oriented appliance and apparatus manufacturers

Thicker cable design meets the requirements of the FT-1 flame test and also approved for the external interconnection of apparatuses and appliances

Flexibility simplifies installation where space is limited

Copper braiding screens the cable against electromagnetic interference

Last Update (13.01.2017)

©2017 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ÖLFLEX® HEAT 180 C MS

### Application range

Areas with high ambient temperatures where insulating and sheath materials of conventional cables will embrittle after a short while

Typical fields of application

- Steel, ceramic and iron works
- Bakery equipment and industrial furnaces
- Electric motor industry
- Sauna/solarium construction
- Thermal and heating elements
- Lighting technology
- Ventilator engineering
- Air-conditioning technology
- Galvanisation technology

### Product features

Halogen-free (IEC 60754-1), no corrosive gases (IEC 60754-2)

Flame-retardant acc. to IEC 60332-1-2, Cable Flame Test, CSA FT 1

Good hydrolysis and UV-resistance

Resistant to a multitude of oils, alcohols, vegetable and animal fats and chemical substances

Adequate ventilation must be ensured, since the mechanical properties of silicone cables decrease from +100°C in the absence of air

### Norm references / Approvals

UL AWM 4476 and cUL AWM II A/B

Construction B, External wiring

UL File No. E63634

### Product Make-up

Fine-wire, tinned-copper conductor

Silicone-based core insulation

Cores twisted together

Tinned-copper screen braiding,  
interleaved plastic foil wrapping

Silicone-based outer sheath,  
colour black

## ÖLFLEX® HEAT 180 C MS

### Technical Data

Classification:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Core identification code:	Colours according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers
Conductor stranding:	Fine wire according to VDE 0295, class 5/IEC 60228 class 5 (Refer to Appendix T16 for the matching US conductor sizes in AWG standard)
Minimum bending radius:	Occasional flexing: 20 x outer diameter Fixed installation: 6 x outer diameter
Nominal voltage:	U <sub>0</sub> /U: 300/500 V Working voltage UL: 600 V
Test voltage:	2000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	According to VDE: -50 °C to +180 °C UL/cUL: up to +150 °C (adequate ventilation required)

### Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

\* Prices are net prices without VAT and surcharges. Sale to business customers.

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)
ÖLFLEX® HEAT 180 C MS			
0046701	3 G 0.5	8.6	43.4
0046702	4 G 0.5	9.3	55.4
0046703	5 G 0.5	10	60.2
0046708	2 X 1	9	48.2
0046709	3 G 1	9.5	65
0046710	4 G 1	10.2	74.6
0046711	5 G 1	11	91.5
0046712	7 G 1	11.9	117.9
0046716	2 X 1.5	9.6	65
0046717	3 G 1.5	10.1	79.4
0046718	4 G 1.5	10.9	101.1
0046719	5 G 1.5	11.8	122.7
0046720	7 G 1.5	12.8	158.7
0046721	12 G 1.5	16.9	245.2
0046723	18 G 1.5	19.6	346.1
0046724	25 G 1.5	23.9	495.7
0046728	3 G 2.5	11	115.5
0046729	4 G 2.5	11.9	146.7
0046730	5 G 2.5	12.9	177.9
0046734	3 G 4	12.3	165.9
0046735	4 G 4	13.4	211.5
0046736	5 G 4	14.9	257.2
0046740	4 G 6	17.2	302.8
0046741	5 G 6	18.7	367.6
0046742	4 G 10	22.8	508.4

Last Update (13.01.2017)  
 ©2017 Lapp Group - Technical changes reserved  
 Product Management [www.lappkabel.de](http://www.lappkabel.de)  
 You can find the current technical data in the corresponding data sheet.  
 PN 0456 / 02\_03\_16

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Lapp Kabel](#) manufacturer:*

Other Similar products are found below :

[M27500-20SP2S23](#) [M3905-BK005](#) [6502FE 8771000](#) [CV6807-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [720451-000](#) [752687-000](#) [83709-002-1000](#) [8469 060100](#) [877541-000](#) [88444-002-1000](#) [9444 060U1000](#) [9497 0001000](#) [9684-060-1000](#) [1302110032](#) [EPD6062-12-9CS1693](#) [EPD-RWC-10972](#) [EPD-RWC-12305](#) [C35473-000](#) [2020D1301-9](#) [219538-6](#) [2412F-010-1000](#) [9534 060U500](#) [29531-010-2000](#) [22759/41-22-9CS2620](#) [259633-000](#) [29529C-010-2000](#) [29532-010-1500](#) [302595-000](#) [CTC-0018-22-9/5-9CS2340](#) [3600B/50 100SF](#) [3644B/16-100SF](#) [CXA-0078-20-3-9CS2405](#) [CXA-0092-14-6/9CS2973](#) [MC6A-16/0.2T2-YWGN](#) [44A0211-20-9CS3030](#) [44A0311-12-9-F871](#) [44A1221-14-9/9-9CS3030](#) [44A1221-16-9/9-9CS3030](#) [44A1321-14-9/9-9CS3030](#) [44A9685-0-F957CS2855](#) [506087-000](#) [5102UE 008500](#) [5201UE 0081000](#) [534553-000](#)