



Standard polyester braided sleeving, expansion rate: 3:1

Helagain HEGPX

Helagain HEGPX is used whenever a higher expansion rate is required. HEGPX is particularly suitable for use in the automotive industry and in electrical appliances.

Features and Benefits

- Made of sturdy polyester
- Highly flexible
- Expansion rate of 3:1
- Easy to apply over irregular shapes
- Good abrasion resistance



Helagain HEGPX braided sleeving.

| | |
|------------------------------|---|
| MATERIAL | Polyester (PET) |
| Operating Temperature | -50 °C to +150 °C, intermittent +220 °C |
| Melting Point | +250 °C |
| Flammability | UL94 V2, FMVSS 302 |
| Specifications | EN 45545: 2013, UL-Recognised |

HF ✓

RoHS ✓



To prevent fraying, the sleeve can be cut with the hot cutting tool HSG0. See page 533.

| TYPE | Bundle Ø min. | Bundle Ø max. | Colour | Reel Length | Article-No. |
|---------|------------------|------------------|------------|----------------|-------------|
| HEGPX06 | 3.0 | 10.0 | Black (BK) | 200 m | 170-00060 |
| HEGPX09 | 5.0 | 16.0 | Black (BK) | 100 m | 170-00090 |
| HEGPX12 | 6.0 | 19.0 | Black (BK) | 100 m | 170-00120 |
| HEGPX20 | 13.0 | 32.0 | Black (BK) | 100 m | 170-00200 |
| HEGPX30 | 19.0 | 45.0 | Black (BK) | 50 m | 170-00300 |
| HEGPX40 | 32.0 | 70.0 | Black (BK) | 50 m | 170-00400 |

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Cuts in any lengths. Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Non-Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[CTA-0053](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-123-06](#) [120-123-10](#) [120-125-12BL](#) [120-125-12R](#) [120-125-20R](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#) [120-105-1-1-06BE](#) [120-105-1-1-06CE](#) [120-116-1-1-06BP](#) [120-116-1-1-10BP](#) [120-116-1-1-12BF](#) [120-123-12](#) [120-125-09](#) [120-125-12](#) [120-125-12Y](#) [120-125-52BL](#) [120-S002-12](#) [HC1B-7008-0375-0](#) [120-S001-09](#) [120-S002-09](#) [121-101-1-1-56BFC](#) [121-101-1-1-64BFC](#) [RAY-90-3.0\(100\)](#) [20675-2](#) [8S42-100FR-CS8184](#) [SAS-115-1-1048-1X](#) [SAS-160-1-1048-1X](#) [25T-GB](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [3-1991136-0](#) [561-SL1000NYGY](#) [561-SL1000PP](#) [561-SL250FRPP](#)