

### Non-Metallic Conduits

- **HG-DC Double Slit**

Control panels, machine building, plant construction and wherever retrofitting is a requirement.


#### Features and Benefits

- Can be opened and closed repeatedly
- Cables can be inserted laterally
- Abrasion resistant
- Free of halogen, sulphur and phosphorus
- Self-extinguishing to IEC 61386
- Colour: black



*HelaGuard HG-DC double slit conduit is ideal for retrofitting.*

|                              |                   |
|------------------------------|-------------------|
| <b>MATERIAL</b>              | Polyamide 6 (PA6) |
| <b>Operating Temperature</b> | -40 °C to +120 °C |
| <b>Flammability</b>          | UL94 V2           |
| <b>Specifications</b>        | IEC 61386         |



*HelaGuard non-metallic conduit*

| TYPE    | Nominal Ø | NW Ø | Outside Ø (OD) | Inside Ø (ID) | Min. Bending Radius (R) | Weight (g/m) | Reel Length | Colour     | Article-No. |
|---------|-----------|------|----------------|---------------|-------------------------|--------------|-------------|------------|-------------|
| HG-DC11 | 11        | 8.5  | 11.5           | 6.2           | 45                      | 23           | 50 m        | Black (BK) | 166-11800   |
| HG-DC13 | 13        | 10   | 13.0           | 7.9           | 55                      | 37           | 50 m        | Black (BK) | 166-11801   |
| HG-DC16 | 16        | 12   | 15.8           | 10.3          | 60                      | 41           | 50 m        | Black (BK) | 166-11802   |
| HG-DC21 | 21        | 17   | 21.2           | 13.9          | 90                      | 63           | 50 m        | Black (BK) | 166-11803   |
| HG-DC28 | 28        | 23   | 28.5           | 20.5          | 105                     | 94           | 50 m        | Black (BK) | 166-11804   |
| HG-DC34 | 34        | 29   | 34.5           | 26.6          | 150                     | 118          | 25 m        | Black (BK) | 166-11805   |
| HG-DC42 | 42        | 36   | 42.5           | 34.8          | 170                     | 193          | 25 m        | Black (BK) | 166-11806   |
| HG-DC54 | 54        | 48   | 54.5           | 45.3          | 170                     | 263          | 25 m        | Black (BK) | 166-11807   |

All dimensions in mm. Subject to technical changes.  
Other reel lengths available on request. Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Non-Heat Shrink Tubing and Sleeves](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CTA-0053](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-123-06](#) [120-123-10](#) [120-125-12BL](#) [120-125-12R](#) [120-125-20R](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#) [120-105-1-1-06BE](#) [120-105-1-1-06CE](#) [120-116-1-1-06BP](#) [120-116-1-1-10BP](#) [120-116-1-1-12BF](#) [120-123-12](#) [120-125-09](#) [120-125-12](#) [120-125-12Y](#) [120-125-52BL](#) [120-S002-12](#) [HC1B-7008-0375-0](#) [120-S001-09](#) [120-S002-09](#) [121-101-1-1-56BFC](#) [121-101-1-1-64BFC](#) [RAY-90-3.0\(100\)](#) [20675-2](#) [8S42-100FR-CS8184](#) [SAS-115-1-1048-1X](#) [SAS-160-1-1048-1X](#) [25T-GB](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [3-1991136-0](#) [561-SL1000NYGY](#) [561-SL1000PP](#) [561-SL250FRPP](#)