

### Non-Metallic Conduits

- HG-SW PA6 Standard Weight

Machine building, plant construction, control panels, public buildings.

#### Features and Benefits


- Very flexible and high fatigue life
- Very abrasion resistant
- High impact strength, recovers if crushed
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus
- Low smoke and low toxicity
- Self-extinguishing according to UL94 V2
- Colour: black (UV resistant); grey on request



HelaGuard PA6 Standard for industrial applications.



One Step to the Web!



HelaGuard non-metallic conduit

<b>MATERIAL</b>	Polyamide 6 (PA6)
<b>Operating Temperature</b>	-40 °C to +120 °C
<b>Operating Temperature Moving</b>	-20 °C to +100 °C
<b>Flammability</b>	UL94 V2
<b>Specifications</b>	IEC 61386, Lloyd's Register, UL-Recognised



TYPE	Nominal Ø	NW Ø	Outside Ø (OD)	Inside Ø (ID)	Min. Bending Radius (R)	Weight (g/m)	Reel Length	Colour	Article-No.
HG-SW10	10	7.5	10.0	6.3	15	19	50 m	Black (BK)	166-11100
HG-SW11	11	8.5	11.5	8.2	20	22	50 m	Black (BK)	166-11101
HG-SW13	13	10	13.0	9.8	25	28	50 m	Black (BK)	166-11102
HG-SW16	16	12	15.8	11.8	35	38	25 m	Black (BK)	166-11110
	16	12	15.8	11.8	35	38	50 m	Black (BK)	166-11103
HG-SW21	21	17	21.2	16.7	45	60	25 m	Black (BK)	166-11111
	21	17	21.2	16.7	45	60	50 m	Black (BK)	166-11104
HG-SW28	28	23	28.5	22.8	50	100	25 m	Black (BK)	166-11105
	28	23	28.5	22.8	50	100	50 m	Black (BK)	166-11112
HG-SW34	34	29	34.5	28.1	60	135	25 m	Black (BK)	166-11106
	34	29	34.5	28.1	60	135	50 m	Black (BK)	166-11118
HG-SW42	42	36	42.5	35.5	70	165	25 m	Black (BK)	166-11113
HG-SW54	54	48	54.5	47.2	80	235	25 m	Black (BK)	166-11114
HG-SW67	67	56	67.2	56.3	130	365	10 m	Black (BK)	166-11109

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Other reel lengths available on request. Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Non-Heat Shrink Tubing and Sleeves](#) category:*

*Click to view products by [Hellermann](#) manufacturer:*

Other Similar products are found below :

[CTA-0053](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-123-06](#) [120-123-10](#) [120-125-12BL](#) [120-125-12R](#) [120-125-20R](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#) [120-105-1-1-06BE](#) [120-105-1-1-06CE](#) [120-116-1-1-06BP](#) [120-116-1-1-10BP](#) [120-116-1-1-12BF](#) [120-123-12](#) [120-125-09](#) [120-125-12](#) [120-125-12Y](#) [120-125-52BL](#) [120-S002-12](#) [HC1B-7008-0375-0](#) [120-S001-09](#) [120-S002-09](#) [121-101-1-1-56BFC](#) [121-101-1-1-64BFC](#) [RAY-90-3.0\(100\)](#) [20675-2](#) [8S42-100FR-CS8184](#) [SAS-115-1-1048-1X](#) [SAS-160-1-1048-1X](#) [25T-GB](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [3-1991136-0](#) [561-SL1000NYGY](#) [561-SL1000PP](#) [561-SL250FRPP](#)