

Storage Rack for HIS-Boxes

HIS-Service Station

HIS general purpose heat shrink tubing provides a reliable insulation and protects against corrosion and mechanical influences. The handy dispenser is ideal for small and medium size projects on-site. The sturdy metal HIS Service Station comes with a cutter and can store all sizes and colours. The Service Station can be mounted to the wall in the work shop or service-van.

Features and Benefits

- Contains up to 5 dispenser boxes
- Place on bench or mount to wall
- Special cutter included for easily cutting tubing length to size



HIS-Service Station contains 5 dispensers and a special cutter.

TYPE	Description	Article-No.
HIS Service Station	HIS-Service Station incl. cutter, contents: 5 dispensers HIS-3 (shrink ratio: 3:1), black, sizes are as follows: HIS-3/1, HIS-6/2, HIS-12/4 (2 pcs.), HIS-24/8	365-30100
HIS Rack/Rite On	HIS-Service Station incl. cutter, contents: 5 dispensers HIS-Pack (shrink ratio: 2:1), black, sizes are as follows: HIS-1/8, HIS-3/16, HIS-1/4, HIS-3/8, HIS 1/2	365-20000
HIS Service Station	HIS-Service Station incl. cutter, empty	300-30000

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Heat Shrinkable Tubing 2:1 on a Reel

HIS-PACK

HIS-PACK is used in general purpose of electrical insulation with a high level of protection against corrosion and mechanical abrasion.

Features and Benefits

- Cross-linked Polyolefin, thin-wall and flexible
- Handy dispenser box including table showing application size range
- Available in black, red, blue, transparent and yellow/green
- 10 sizes from 1.2 mm to 25.4 mm



HIS-PACK.




Detailed Information about Heatguns please refer to page 529.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	2:1
Operating Temperature	-55 °C to +125 °C
Minimum Shrink Temperature	+100 °C
Longitudinal change after shrinkage	+/- 5 %
Dielectric Strength	20kV/mm according to ASTM D2671
Flammability	UL224 VW-1 (except clear)
Specifications	SAE - AMS - DTL-23053/5 Class 1 and 3, SAE - AMS - DTL-23053/5 Class 2 (clear), UL224 125 °C 600V VW-1



For product specific approvals and specifications please refer to the Appendix.





Heat Shrinkable Tubing 2:1 on a Reel

HIS-PACK

TYPE	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
HIS-PACK-1.2/0.6	1.2	3/64 "	0.6	0.40	10 m	Black (BK)	300-30120
	1.2	3/64 "	0.6	0.40	10 m	Blue (BU)	300-30126
	1.2	3/64 "	0.6	0.40	10 m	Red (RD)	300-30122
	1.2	3/64 "	0.6	0.40	10 m	Transparent (CL)	300-30123
HIS-PACK-1.6/0.8	1.6	1/16 "	0.8	0.40	10 m	Black (BK)	300-30160
	1.6	1/16 "	0.8	0.40	10 m	Blue (BU)	300-30166
	1.6	1/16 "	0.8	0.40	10 m	Red (RD)	300-30162
	1.6	1/16 "	0.8	0.40	10 m	Transparent (CL)	300-30163
HIS-PACK-2.4/1.2	2.4	3/32 "	1.2	0.50	10 m	Black (BK)	300-30240
	2.4	3/32 "	1.2	0.50	10 m	Blue (BU)	300-30246
	2.4	3/32 "	1.2	0.50	10 m	Red (RD)	300-30242
	2.4	3/32 "	1.2	0.50	10 m	Transparent (CL)	300-30243
HIS-PACK-3.2/1.6	3.2	1/8 "	1.6	0.50	10 m	Black (BK)	300-30320
	3.2	1/8 "	1.6	0.50	10 m	Blue (BU)	300-30326
	3.2	1/8 "	1.6	0.50	10 m	Green-Yellow (GNYE)	300-30327
	3.2	1/8 "	1.6	0.50	10 m	Red (RD)	300-30322
	3.2	1/8 "	1.6	0.50	10 m	Transparent (CL)	300-30323
HIS-PACK-4.8/2.4	4.8	3/16 "	2.4	0.50	10 m	Black (BK)	300-30480
	4.8	3/16 "	2.4	0.50	10 m	Blue (BU)	300-30486
	4.8	3/16 "	2.4	0.50	10 m	Green-Yellow (GNYE)	300-30487
	4.8	3/16 "	2.4	0.50	10 m	Red (RD)	300-30482
	4.8	3/16 "	2.4	0.50	10 m	Transparent (CL)	300-30483
HIS-PACK-6.4/3.2	6.4	1/4 "	3.2	0.60	5 m	Black (BK)	300-30640
	6.4	1/4 "	3.2	0.60	5 m	Blue (BU)	300-30646
	6.4	1/4 "	3.2	0.60	5 m	Green-Yellow (GNYE)	300-30647
	6.4	1/4 "	3.2	0.60	5 m	Red (RD)	300-30642
	6.4	1/4 "	3.2	0.60	5 m	Transparent (CL)	300-30643
HIS-PACK-9.5/4.7	9.5	3/8 "	4.7	0.60	5 m	Black (BK)	300-30950
	9.5	3/8 "	4.7	0.60	5 m	Blue (BU)	300-30956
	9.5	3/8 "	4.7	0.60	5 m	Green-Yellow (GNYE)	300-30957
	9.5	3/8 "	4.7	0.60	5 m	Red (RD)	300-30952
	9.5	3/8 "	4.7	0.60	5 m	Transparent (CL)	300-30953
HIS-PACK-12.7/6.4	12.7	1/2 "	6.4	0.60	5 m	Black (BK)	300-31270
	12.7	1/2 "	6.4	0.60	5 m	Blue (BU)	300-31276
	12.7	1/2 "	6.4	0.60	5 m	Green-Yellow (GNYE)	300-31277
	12.7	1/2 "	6.4	0.60	5 m	Red (RD)	300-31272
	12.7	1/2 "	6.4	0.60	5 m	Transparent (CL)	300-31273
HIS-PACK-19.1/9.5	19.1	3/4 "	9.5	0.80	5 m	Black (BK)	300-31900
	19.1	3/4 "	9.5	0.80	5 m	Blue (BU)	300-31906
	19.1	3/4 "	9.5	0.80	5 m	Green-Yellow (GNYE)	300-31907
	19.1	3/4 "	9.5	0.80	5 m	Red (RD)	300-31902
	19.1	3/4 "	9.5	0.80	5 m	Transparent (CL)	300-31903
HIS-PACK-25.4/12.7	25.4	1 "	12.7	0.90	5 m	Black (BK)	300-32540
	25.4	1 "	12.7	0.90	5 m	Blue (BU)	300-32546
	25.4	1 "	12.7	0.90	5 m	Green-Yellow (GNYE)	300-32547
	25.4	1 "	12.7	0.90	5 m	Red (RD)	300-32542
	25.4	1 "	12.7	0.90	5 m	Transparent (CL)	300-32543

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR6145-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [617867N001](#) [6500750004](#) [D-306-38](#) [770-003S106W2](#) [770-007A303](#)
[770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [MFT-MT2000-NO.14-0-SP](#) [MFT-MT2000-NO.65-X-SP](#)
[MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#)
[MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-](#)
[1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-](#)
[316-6"-Clear](#) [FP301-332-6"-Black](#) [FP301-3/8-6"-Clear](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#) [121-018-40](#) [121-123-1-1-32BTC](#) [121-](#)
[123-1-1-40BTC](#) [121-127-09BK](#)