



Storage Rack for HIS-Boxes

HIS-Service Station

HIS general purpose heat shrink tubing provides a reliable insulation and protects against corrosion and mechanical influences. The handy dispenser is ideal for small and medium size projects on-site. The sturdy metal HIS Service Station comes with a cutter and can store all sizes and colours. The Service Station can be mounted to the wall in the work shop or service-van.

Features and Benefits

- Contains up to 5 dispenser boxes
- Place on bench or mount to wall
- Special cutter included for easily cutting tubing length to size



HIS-Service Station contains 5 dispensers and a special cutter.

| TYPE | Description | Article-No. |
|----------------------------|--|-------------|
| HIS Service Station | HIS-Service Station incl. cutter, contents: 5 dispensers HIS-3 (shrink ratio: 3:1), black, sizes are as follows: HIS-3/1, HIS-6/2, HIS-12/4 (2 pcs.), HIS-24/8 | 365-30100 |
| HIS Rack/Rite On | HIS-Service Station incl. cutter, contents: 5 dispensers HIS-Pack (shrink ratio: 2:1), black, sizes are as follows: HIS-1/8, HIS-3/16, HIS-1/4, HIS-3/8, HIS 1/2 | 365-20000 |
| HIS Service Station | HIS-Service Station incl. cutter, empty | 300-30000 |

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Heat Shrinkable Tubing 2:1 on a Reel

HIS-PACK

HIS-PACK is used in general purpose of electrical insulation with a high level of protection against corrosion and mechanical abrasion.

Features and Benefits

- Cross-linked Polyolefin, thin-wall and flexible
- Handy dispenser box including table showing application size range
- Available in black, red, blue, transparent and yellow/green
- 10 sizes from 1.2 mm to 25.4 mm



HIS-PACK.




Detailed Information about Heatguns please refer to page 529.

| | |
|--|--|
| MATERIAL | Polyolefin, cross-linked (PO-X) |
| Shrink Ratio | 2:1 |
| Operating Temperature | -55 °C to +125 °C |
| Minimum Shrink Temperature | +100 °C |
| Longitudinal change after shrinkage | +/- 5 % |
| Dielectric Strength | 20kV/mm according to ASTM D2671 |
| Flammability | UL224 VW-1 (except clear) |
| Specifications | SAE - AMS - DTL-23053/5 Class 1 and 3, SAE - AMS - DTL-23053/5 Class 2 (clear), UL224 125 °C 600V VW-1 |



For product specific approvals and specifications please refer to the Appendix.





Heat Shrinkable Tubing 2:1 on a Reel

HIS-PACK

| TYPE | Supplied Ø D min. | Size (imperial) | Recov. Ø d max. | Wall (WT) | Reel Length | Colour | Article-No. |
|--------------------|----------------------|--------------------|--------------------|--------------|----------------|---------------------|-------------|
| HIS-PACK-1.2/0.6 | 1.2 | 3/64 " | 0.6 | 0.40 | 10 m | Black (BK) | 300-30120 |
| | 1.2 | 3/64 " | 0.6 | 0.40 | 10 m | Blue (BU) | 300-30126 |
| | 1.2 | 3/64 " | 0.6 | 0.40 | 10 m | Red (RD) | 300-30122 |
| | 1.2 | 3/64 " | 0.6 | 0.40 | 10 m | Transparent (CL) | 300-30123 |
| HIS-PACK-1.6/0.8 | 1.6 | 1/16 " | 0.8 | 0.40 | 10 m | Black (BK) | 300-30160 |
| | 1.6 | 1/16 " | 0.8 | 0.40 | 10 m | Blue (BU) | 300-30166 |
| | 1.6 | 1/16 " | 0.8 | 0.40 | 10 m | Red (RD) | 300-30162 |
| | 1.6 | 1/16 " | 0.8 | 0.40 | 10 m | Transparent (CL) | 300-30163 |
| HIS-PACK-2.4/1.2 | 2.4 | 3/32 " | 1.2 | 0.50 | 10 m | Black (BK) | 300-30240 |
| | 2.4 | 3/32 " | 1.2 | 0.50 | 10 m | Blue (BU) | 300-30246 |
| | 2.4 | 3/32 " | 1.2 | 0.50 | 10 m | Red (RD) | 300-30242 |
| | 2.4 | 3/32 " | 1.2 | 0.50 | 10 m | Transparent (CL) | 300-30243 |
| HIS-PACK-3.2/1.6 | 3.2 | 1/8 " | 1.6 | 0.50 | 10 m | Black (BK) | 300-30320 |
| | 3.2 | 1/8 " | 1.6 | 0.50 | 10 m | Blue (BU) | 300-30326 |
| | 3.2 | 1/8 " | 1.6 | 0.50 | 10 m | Green-Yellow (GNYE) | 300-30327 |
| | 3.2 | 1/8 " | 1.6 | 0.50 | 10 m | Red (RD) | 300-30322 |
| | 3.2 | 1/8 " | 1.6 | 0.50 | 10 m | Transparent (CL) | 300-30323 |
| HIS-PACK-4.8/2.4 | 4.8 | 3/16 " | 2.4 | 0.50 | 10 m | Black (BK) | 300-30480 |
| | 4.8 | 3/16 " | 2.4 | 0.50 | 10 m | Blue (BU) | 300-30486 |
| | 4.8 | 3/16 " | 2.4 | 0.50 | 10 m | Green-Yellow (GNYE) | 300-30487 |
| | 4.8 | 3/16 " | 2.4 | 0.50 | 10 m | Red (RD) | 300-30482 |
| | 4.8 | 3/16 " | 2.4 | 0.50 | 10 m | Transparent (CL) | 300-30483 |
| HIS-PACK-6.4/3.2 | 6.4 | 1/4 " | 3.2 | 0.60 | 5 m | Black (BK) | 300-30640 |
| | 6.4 | 1/4 " | 3.2 | 0.60 | 5 m | Blue (BU) | 300-30646 |
| | 6.4 | 1/4 " | 3.2 | 0.60 | 5 m | Green-Yellow (GNYE) | 300-30647 |
| | 6.4 | 1/4 " | 3.2 | 0.60 | 5 m | Red (RD) | 300-30642 |
| | 6.4 | 1/4 " | 3.2 | 0.60 | 5 m | Transparent (CL) | 300-30643 |
| HIS-PACK-9.5/4.7 | 9.5 | 3/8 " | 4.7 | 0.60 | 5 m | Black (BK) | 300-30950 |
| | 9.5 | 3/8 " | 4.7 | 0.60 | 5 m | Blue (BU) | 300-30956 |
| | 9.5 | 3/8 " | 4.7 | 0.60 | 5 m | Green-Yellow (GNYE) | 300-30957 |
| | 9.5 | 3/8 " | 4.7 | 0.60 | 5 m | Red (RD) | 300-30952 |
| | 9.5 | 3/8 " | 4.7 | 0.60 | 5 m | Transparent (CL) | 300-30953 |
| HIS-PACK-12.7/6.4 | 12.7 | 1/2 " | 6.4 | 0.60 | 5 m | Black (BK) | 300-31270 |
| | 12.7 | 1/2 " | 6.4 | 0.60 | 5 m | Blue (BU) | 300-31276 |
| | 12.7 | 1/2 " | 6.4 | 0.60 | 5 m | Green-Yellow (GNYE) | 300-31277 |
| | 12.7 | 1/2 " | 6.4 | 0.60 | 5 m | Red (RD) | 300-31272 |
| | 12.7 | 1/2 " | 6.4 | 0.60 | 5 m | Transparent (CL) | 300-31273 |
| HIS-PACK-19.1/9.5 | 19.1 | 3/4 " | 9.5 | 0.80 | 5 m | Black (BK) | 300-31900 |
| | 19.1 | 3/4 " | 9.5 | 0.80 | 5 m | Blue (BU) | 300-31906 |
| | 19.1 | 3/4 " | 9.5 | 0.80 | 5 m | Green-Yellow (GNYE) | 300-31907 |
| | 19.1 | 3/4 " | 9.5 | 0.80 | 5 m | Red (RD) | 300-31902 |
| | 19.1 | 3/4 " | 9.5 | 0.80 | 5 m | Transparent (CL) | 300-31903 |
| HIS-PACK-25.4/12.7 | 25.4 | 1 " | 12.7 | 0.90 | 5 m | Black (BK) | 300-32540 |
| | 25.4 | 1 " | 12.7 | 0.90 | 5 m | Blue (BU) | 300-32546 |
| | 25.4 | 1 " | 12.7 | 0.90 | 5 m | Green-Yellow (GNYE) | 300-32547 |
| | 25.4 | 1 " | 12.7 | 0.90 | 5 m | Red (RD) | 300-32542 |
| | 25.4 | 1 " | 12.7 | 0.90 | 5 m | Transparent (CL) | 300-32543 |

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR6145-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [617867N001](#) [6500750004](#) [D-306-38](#) [770-003S106W2](#) [770-007A303](#)
[770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [MFT-MT2000-NO.14-0-SP](#) [MFT-MT2000-NO.65-X-SP](#)
[MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#)
[MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [FP301-3/8-6"-Clear](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#) [121-018-40](#) [121-123-1-1-32BTC](#) [121-123-1-1-40BTC](#) [121-127-09BK](#)